

SPS-0536 REV B POLLOCK NO. 7 JOB NAME: FIXTURE TYPE:									
	A		В	С		D	E	F	
Order Example	e: BLE - C - DBW10 - 1007	- SBK - NA - I	NA - 350 - E26						
SBK SWH CSB CSW CMG CSR CRZ CSBW CSBW CSBG CSBP CSGW CSUW CSBB NON-CSA OPTIONS: TBK TWH TBR TRD	8" Shade ¹ 10" Shade 12" Shade 5D CORD OPTIONS: Standard Black Standard White Black Cloth White Cloth Grey Cloth Red Cloth Red Cloth Red Cloth Black & White Cloth Black & White Cloth Black & Pink Cloth Black & Pink Cloth Black & Brown Cloth Black & Brown Cloth	NA WC ACR D - SHAI Please Note: in Section C Finish is selei coat painted- NA	DE ACCESSORY Not Applicable Wire Cage Acrylic Diffuser DE ACCESSORY If no Shade Accessory please select MA. If P cted, accessory will be to-match Not Applicable R COAT FINISH Black Textured Black White Matte Black White Matte Black White Matte White Dark Green Emerald Green Jadite Mint Chartreuse Teal Barn Red Orange Watermelon Blush Pink Magenta Sherbet Orang Buttery Yellow Sunflower	FINISH is selected orcelain powder IES:	(CONTINU POWDER 601 605 615 700 705 710 715 790 800 805 810 975	PE ACCESSORY FIN ED) R COAT FINISHES: Chocolate Rust Oil-Rubbed Bronze Royal Blue Navy Cobalt Blue Delphite Blue Lavender Industrial Grey Charcoal Granite Graphite Galvanized AIN FINISHES: Black White Vintage Green Jadite Cherry Red Yellow Bronze Cobalt Blue Delphite Blue Graphite Metallic Chrome	150 250 350 355 455 550 650 750 765 850 950	NOPY FINISH Black White Vintage Green Jadite Cherry Red Yellow Bronze Cobalt Blue Delphite Blue Graphite Metallic Chrome CKET TYPE 200 Watt Max 23 Watt Max ^{1,5}	

IMPORTANT: (1) Not available with Acrylic Diffuser option (2) Not available with GU24 Socket Type (3) Acrylic Diffuser accessory reduces incandescent wattage to 60W (4) Fixture is UL Listed for Damp Locations with Acrylic Diffuser (5) Fixtures configured with GU24 socket are non-returnable

MOUNTING DIMENSIONS





BARN LIGHT ELECTRIC CO.

SPECIFICATIONS

CERTIFICATIONS, LISTINGS & WARRANTY

MADE IN THE USA

Manufactured and Hand-Crafted in Our 60,000 Square Foot Facility Located in Titusville, Fl

CSA LISTED FOR DAMP LOCATIONS ACR is UL Listed for Damp Locations

LIMITED WARRANTY For Additional Information on Our Limited Warranty, Please See Our Terms & Conditions

CONSTRUCTION & FINISH

SHADE & CANOPY Hand-Spun from 20 Gauge Porcelain Steel

PORCELAIN FINISHES Applied by Hand and Fired in a High Temperature Oven

POWDER COAT FINISHES Polyester Powder Coat Finishes Are Electro-Statically Applied and Thermocured

CORD

Cord-hung Pendants Include 7' of Standard Cord or 5' Of Cotton Cord, +/- For Socket Orientation

LIGHT SOURCE

INCANDESCENT Medium Base E26 Socket, 120 VAC, 200 Watt Max

COMPACT FLUORESCENT Bi-Pin Base GU24 Socket, 120 VAC, 23 Watt Max