WAC LIGHTING

1" LEDme

Square Open Reflector Downlight w/ Integral Driver

	Fixture Type:
-	Catalog Number:
	Project:
	Location:
-	·

Model	Color Temp & CRI	Lumens	CBCP	Finish
HR-LED251E	27 2700K - 85 30 3000K - 85 35 3500K - 85 40 4000K - 85	245 250 270 285	530 540 573 608	BN Brushed Nickel GM Gun Metal WT White

Example: HR-LED251E-27-BN

DESCRIPTION

Perfect for ceilings, under cabinet and wall niches. LED Miniature Recessed Downlights offer a super low profile and Die-cast aluminum trim with a 25° cutoff angle for comfortablegeneral and task lighting.

FEATURES

- New Construction, may be re-configured in the field for Remodel
- Driver required
- 5 year warranty

SPECIFICATIONS

Construction: Die-cast aluminum trim, aluminum heat sink and 20

gauge steel housing painted black.

Power: 4W

Input: 120 VAC, 50/60Hz
Dimming: ELV: 100-10%
Light Source: Integrated LED

3 Step Mac Adam Ellipse

Rated Life: 80000 Hours

Mounting: Heavy gauge retention clips secures housing firmly to

ceiling

Cut Out: 2 1/2"

Finish: Electroplated:Brushed Nickel, Electroplated::Gun Metal,

 ${\sf Electroplated:::White}$

Ceiling Thickness: 1/2" - 1"

Operating Temp: -4°F to 104°F (-20°C to 40°C)

Standards: UL, cUL, Damp Location Listed, IC



FINISHES:





Gun Metal



Brushed Nickel

White

LINE DRAWING:

