# WAC LIGHTING

### **163LED**

## Low Voltage Track Luminaire

System Type & Model & Wattage Finish

Voltage

Voltage			
HHT H Track - 120 VAC JHT J/J2 Track - 120 VAC LHT L Track - 120 VAC	163LED 8W	WT White	

Example: HHT-163LED-WT

#### **DESCRIPTION**

Form follows function with instrument-like design and technology of the Range low voltage spot. Engineered to precision, these specification grade luminaires are ideal for commercial, hospitality and retail applications where high-performance and versatility are required. Low Voltage track fixture offered in a wide variety of styles and finishes for a multitude of lighting applications in residential, retail, commercial and hospitality environments. Available in H, J/J2, and L style track configurations. Built-in transformer has a 1W minimum load and can be installed with an LED lamp.

#### **FEATURES**

- 350° horizontal rotation and 90° vertical aiming with built-in degree scales
- Two screws for locking aiming angle
- · 38° beam spread
- Fully enclosed back to prevent light leaks
- Easily re-lamped from the front
- Accommodates 1 lens or 1 accessory
- LED model includes 8W MR16 LED lamp
- Beam Angle: 35 deg
- Transformer concealed within the fixture

#### **SPECIFICATIONS**

**Construction:** Die-cast aluminum track head with polycarbonate

transformer case and track adapter. Bi-pin ceramic socket

for MR16 lamp.

Power: 8W

**Input:** 120 VAC, 50/60Hz **Dimming:** ELV: 100-15%

Light Source: LED MR16 (Included)


3 Step Mac Adam Ellipse

Rated Life: 50000 Hours

Finish: Electrostatically powder Coated: White

Operating Temp: -4°F to 104°F (-20°C to 40°C)

Standards: UL, cUL, Dry Location Listed






#### FINISHES:



White

#### **LINE DRAWING:**





# **163LED**

Low Voltage Track Luminaire

Fixture Type:	
Catalog Number:	
Project:	
Location:	

#### ACCESSORIES

	Model	Description	Finish
•••	LENS-16-RED LENS-16-GRN LENS-16-BLU LENS-16-AMB	Colored Lens Colored Lens Colored Lens Colored Lens	Red Green Blue Amber
	LENS-16-FR	Clear/Frosted Lens	Frosted
	LENS-16-SPR	Spread Lens	Spread Lens
	LENS-16-UVF	UV Filter lens	Clear
	LENS-16-BEL	Beam Elongating Lens	Beam Elongating
	LENS-16-HCL	Honeycomb Louver	Black