WAC LIGHTING

7"/11"/15" Round

Ceiling and Wall Mount

Fixture Type:

Catalog Number:

Project:

Location:

Model & Size	Color Temp & CRI	Watt	Lumens	Finish	
FM-07RN 7"	930 3000K - 90 935 3500K - 90	15W 15W	1100 1100	BK Black BN Brushed Nickel	
FM-11RN 11"	930 3000K - 90 935 3500K - 90	20W 20W	1525 1525	BZ Bronze WT White	
FM-15RN 15"	930 3000K - 90 935 3500K - 90	28W 28W	2550 2550		

Example: FM-07RN-930-BK

DESCRIPTION

Ultra-slim flush mount that uses edge-lit technology and a translucent diffuser for uniform illumination without shadows or hotspots.

FEATURES

- Multiple LED array for uniform illumination
- Driver installed within the Junction Box, driver dimension: 2.25" dia x 1" deep
- 5 year warranty

SPECIFICATIONS

Construction:	Aluminum with translucent diffuser		
Power:	15W, 20W, 28W		
Input:	120 VAC, 50/60Hz		
Dimming:	ELV: 100-5% , TRIAC: 100-5%		
Light Source:	Integrated LED		
Lens:	Translucent acrylic diffuser		
Rated Life:	50000 Hours		
Mounting:	Installs over a 3", 4" or 3/0-4/0 hybrid junction box, Can be mounted on ceiling or wall in all orientations		
Finish:	Electrostatically Powder Coated:White, Electrostatically Powder Coated::Bronze, Electrostatically Powder Coated:::Brushed Nickel, Electrostatically Powder Coated::::Black		
Operating Temp:	-4°F to 104°F (-20°C to 40°C)		
Standards:	UL, cUL, Damp Location Listed, Energy Star 2.0, Title 24 JA8-2019 Compliant, ADA		



FINISHES:



LINE DRAWING:

