

WAC LIGHTING

BLO G2

Ceiling and Wall Mount

Model & Size	Color Temp & CRI	Lumens	Finish
FM-113G2 13"	2700K 90	1370	WT White
FM-115G2 15"	2700K 90	1960	
	3000K 90	1500	
	3000K 90	1900	
	3500K 90	1650	
	3500K 90	2300	

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Example: **FM-113G2-27-WT**

DESCRIPTION

Multiple high-powered LEDs illuminate the acrylic diffuser uniformly without socket shadows which are common in conventional flush mounts.

FEATURES

- Multiple LED array for uniform illumination
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Construction:	Aluminum with white acrylic diffuser
Power:	20W, 27W
Input:	120-277 VAC, 50/60Hz
Dimming:	ELV: 100-5% , TRIAC: 100-5%
Light Source:	Integrated LED
Lens:	Translucent acrylic diffuser
Rated Life:	50000 Hours
Mounting:	Installs over a 3" or 4" Junction Box, Can be mounted on ceiling or wall in all orientations
Finish:	Electrostatically Powder Coated: White
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Damp Location Listed, Energy Star 2.0, Title 24 JA8-2019 Compliant, ADA



FINISHES:



White

REPLACEMENT PARTS

RPL-SHA-113G2 - 13" Replacement Shade