WAC LIGHTING

Compass

Indoor/Outdoor Ceiling And Wall Mount 3000K

Model FM- Fixture Type:

Catalog Number:

Project:

Location:

el & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
I-W33612 12"	3000K	AL Brushed Aluminum	19W	1647	1147

Example: FM-W33612-AL

•For 277V special order, add an "F" before the finish: FM-W33612F-AL

For custom requests please contact customs@waclighting.com

DESCRIPTION

Designed with the precision engineering and robust performance of the magnetic instrument created to determine direction. Compass offers a contemporary form created with meticulousattention to detail. Appealing aluminum frame embraces mouth blown etched opal glass diffusing ambient light for ceiling or walls, depending upon specification requirements.

FEATURES

- ACLED driverless technology
- 5 year warranty


SPECIFICATIONS

Color Temp:	3000K
Input:	120 VAC,50/60Hz
CRI:	90
Dimming:	ELV: 100-10%
Rated Life:	50000 Hours
Mounting:	Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL,IP65
	Wet Location Listed
Construction:	Aluminum hardware with etched opal glass diffuser



FINISHES:





FM-W33612

WAC LIGHTING

Compass

Indoor/Outdoor Ceiling And Wall Mount 3000K

Mode FΝ

	Fixtu	re 1	Гур	e:
--	-------	------	-----	----

Catalog Number:

Project:

Location:

del & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
FM-W33616 16"	3000K	AL Brushed Aluminum	35W	3112	1668

Example: FM-W33616-AL

•For 277V special order, add an "F" before the finish: FM-W33616F-AL

For custom requests please contact customs@waclighting.com

DESCRIPTION

Designed with the precision engineering and robust performance of the magnetic instrument created to determine direction. Compass offers a contemporary form created with meticulousattention to detail. Appealing aluminum frame embraces mouth blown etched opal glass diffusing ambient light for ceiling or walls, depending upon specification requirements.

FEATURES

- ACLED driverless technology
- 5 year warranty


SPECIFICATIONS

Color Temp:	3000K
Input:	120 VAC,50/60Hz
CRI:	90
Dimming:	ELV: 100-10%
Rated Life:	50000 Hours
Mounting:	Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL
	Wet Location Listed
Construction:	Aluminum hardware with etched opal glass diffuser



FINISHES:





FM-W33616