



T721LED

14" X 14" SQUARE SLIM LED CANOPY

JOB INFORMATION

Type: _____
 Catalog No: _____
 Project Name: _____
 Comments: _____
 Prepared by: _____

T721LED

FEATURES

USE OF PRODUCT

The intended use of this product is in parking areas, entrances, walkways, underpasses, loading docks, or recreation areas.

HOUSING

Die-cast aluminum housing with knockout located on all side.

FINISH

Matt-finished, architectural bronze powdercoat over a precise chromate conversion coating. Available in standard dark polyester bronze or consult factory for made to order architectural finishes.

OPTICS

One-piece white powdercoat reflector with polycarbonate lens. Lens is sealed by one-piece silicon gasket prohibits entrance of outside contaminants.

LED

High output LEDs offer a minimum estimated operating life of 50,000 hours in 5000K with CRI>83; Efficacy: 113lm/W. LEDs placed on high performance aluminum heatsink for reduced junction temperatures and extended life.

DRIVER

Durable and long lasting LED dimmable driver operates at 120-277V; Power factor: 0.94; 50 to 60 Hz. -30°C Min Temp. to 40°C Max Temp.

MOUNTING

T721LED may be pendant hung(we accept 1/2" thread) or surface mount.

EPA

Effective Projected Area (Sq. Ft.): 0.632 ft²

Weight

13 Lbs

LISTINGS/COMPLIANCE

- CEC Compliant emergency drive
- CSA - Suitable for wet location

ORDERING INFO

SERIES	WATT/LUMENS	VOLTAGE	COLOR TEMPERATURE	FINISH	MOUNTING	OPTIONS
T721LED	10 - 10W/1016lm	UNV - 120V-277V	30 - 3000K	BZ ¹ - Bronze	S - Surface Mount	PC1 - Photocell 120V
	18 - 18W/1875lm	347 - 347V	35 - 3500K	MTO ² - Made to order	P ³ - Pendant hung	PC2 - Photocell 277V
	30 - 30W/2810lm	480 - 480V	40 - 4000K	MGTO ² - Marin grade		MS - Motion sensor (Bi-Level)
	40 - 40W/3587lm		50 - 5000K	made to order		SP10 - Surge Protection 10KV
	58 - 58W/5155lm					EM - Emergency battery (integral)
	84 - 84W/7575lm					DS - Dark Sky

Notes

1. Standard
2. RAL number required.
3. 18" standard pendant.

T721LED

14" X 14" SQUARE SLIM LED CANOPY

DIMENSIONS

