



T730LEDB

SQUARE SLIM LED CANOPY

JOB INFORMATION

Type: _____
 Catalog No: _____
 Project Name: _____
 Comments: _____
 Prepared by: _____

T730LEDB

FEATURES

USE OF PRODUCT

The intended use of this product is in parking areas, entrances, walkways, underpasses, loading docks, or recreation areas.

HOUSING

Sealed die-cast aluminum housing with knockout located on side.

FINISH

Matt-finished, architectural bronze powdercoat over a precise chromate conversion coating. Available in standard dark polyester bronze or consult factory for made to order architectural finishes.

OPTICS

One-piece white powdercoat reflector with polycarbonate lens. Lens is sealed by one-piece silicon gasket prohibits entrance of outside contaminants.

LED

High output LEDs offer a minimum estimated operating life of 50,000 hours in 4000K, 5000K with CRI>70; LEDs placed on high performance aluminum heatsink for reduced junction temperatures and extended life.

DRIVER

Durable and long lasting LED driver operates at 120-277V with 0-10V dimming driver, -40°C Min Temp. +40°C Max Temp.

LISTINGS/COMPLIANCE

- UL - Suitable for wet locations.
- DLC

ORDERING INFO

| SERIES | WATT/LUMENS | VOLTAGE | COLOR TEMPERATURE | FINISH | OPTIONS |
|---------|-----------------|------------------------------|-------------------|---|-------------------------------|
| T730LED | 40 - 40W/5450lm | UNV ¹ - 120V-277V | 40 - 4000K | BZ ² - Bronze | MS - Motion sensor (Bi-Level) |
| | 60 - 60W/8000lm | 347 - 347-480V | 50 - 5000K | MTO ³ - Made to order MGTO ³ - Marin grade made to order | EM - Emergency battery |

Notes

1. DLC only available in 120-277V
2. Standard
3. RAL number required.

T730LEDB

DIMENSIONS

