



T884LED

AVANTI LED BOLLARD

JOB INFORMATION

Type: _____
 Catalog No: _____
 Project Name: _____
 Comments: _____
 Prepared by: _____

T884LED

FEATURES

USE OF PRODUCT

The intended use of this product is to accentuate landscape areas, pedestrian pathways, and entranceways. It is an excellent source to guide walkways or driveways.

HOUSING

Rugged heavy-gage cast, spun, and extruded aluminum.

FINISH

Matt-finished, thermoset polyester oven baked powdercoat finish. Available in standard dark polyester bronze finish for impact, corrosion, and UV resistance. Consult factory for made to order architectural finishes.

OPTICS

- Distribution is 360°, using a special nautically-styled polycarbonate lens. Also available with an internal dome reflector.
- Rubber gasketing seals the lens to the housing to prevent entrance of outside contaminants.

LED

High output LEDs offer a minimum estimated operating life of 50,000 hours in 3000K, 3500K, 4000K, or 5000K (standard) with CRI>83. LEDs placed on high performance aluminum heatsink for reduced junction temperatures and extended life.

DRIVER

Durable and long lasting LED driver operates at 120-277V and boasts a 90% power factor at 50 to 60 Hz with 0-10V Dimming Constant Current. Driver protections includes: Output open load, over-current and short-circuit, and over-temperature with auto recovery. -30°C Min Temp. to 40°C Max Temp. Step down transformer may be utilized for 480V or 347V applications.

MOUNTING

- Bollard must be mounted on a concrete base. (Supplied by others)

LISTINGS/COMPLIANCE

- CEC Compliant emergency drive
- CSA - Suitable for wet locations

ANCHOR BASE & BOLT

Three 3/8"x 12" galvanized anchor bolts are supplied, complete with two nuts and washers. The anchor base plate is made of heavy-duty aluminum.



ORDERING INFO

SERIES	HEIGHT	WATT/LUMENS	VOLTAGE	COLOR TEMPERATURE	FINISH	OPTIONS	
T884LED	42 - 42"	10 - 10W/1050lm	UNV - 120-277V	30 - 3000K	BZ ³ - Bronze	0 - No Ring	1. Length Required. 2. Standard color temperature. 3. Standard finish. 4. RAL number required.
	MTO ¹ - Made to order	18 - 18W/1890lm	347 - 347V	35 - 3500K	MTO ⁴ - Made to order	1 - One Ring	
		30 - 30W/3150lm	480 - 480V	40 - 4000K		2 - Two Rings	
				50 ² - 5000K			

T877LED

STAINLESS STEEL LED BOLLARD WITH LOUVER

DIMENSIONS

