



T889LED

NOBLE LED BOLLARD

JOB INFORMATION

Type: _____
 Catalog No: _____
 Project Name: _____
 Comments: _____
 Prepared by: _____

T889LED

FEATURES

USE OF PRODUCT

The intended use of this product is for pathways, parking lots, plazas, entrance ways, parks, and as landscape accents.

HOUSING

Aluminum housing.

LOUVER

Rugged aluminum external 360° around bollard. 180° louvers available upon request.

FINISH

Matt-finished, thermoset polyester oven-baked powdercoat finish. Available in standard dark polyester bronze or consult factory for made to order architectural finishes.

OPTICS

- Available "house side" cut-off shield (please see options)
- Rubber gasketing seals the lens to the housing to prevent entrance of outside contaminants.

LED

High output LEDs offer a minimum estimated operating life of 50,000 hours in 3000K, 3500K,

4000K, or 5000K (standard) with CRI>83. LEDs placed on high performance aluminum heatsink for reduced junction temperatures and extended life.

DRIVER

Durable and long lasting LED driver operates at 120-277V and boasts a 90% power factor at 50 to 60 Hz with 0-10V Dimming Constant Current. Driver protections includes: Output open load, over-current and short-circuit, and over-temperature with auto recovery. -30°C Min Temp. to 40°C Max Temp. Step down transformer may be utilized for 480V or 347V applications.

MOUNTING

- Bollard must be mounted on a concrete base. (Supplied by others)

ANCHOR BASE & BOLT

Four 3/8" by 12" galvanized anchor bolts are supplied, complete with two nuts and washers. The anchor base plate is constructed heavy-duty aluminum.

LISTINGS/COMPLIANCE

- CEC Complaint emergency drive
- ETL Listed or UL-Suitable for wet locations



ORDERING INFO

SERIES	HEIGHT	DIAMETER	WATT/LUMENS	VOLTAGE	COLOR TEMPERATURE	FINISH	OPTIONS
T889LED	42 - 42" MTO ¹ - Made to order	8 - 8" Diameter 10 - 10" Diameter	10 - 10W/1050lm	UNV - 120V-277V	30 - 3000K	BZ ³ - Bronze	PC1 - Photocell 120V
			18 - 18W/1890lm	347 - 347V	35 - 3500K	MTO ⁴ - Made to order	PC2 - Photocell 277V
			30 - 30W/3105lm	480 - 480V	40 - 4000K	MGTO ⁴ - Marin grade	EM - Emergency battery
			45 - 45W/4725lm		50 ² - 5000K	made to order	CEM - Cold pack emergency battery SP10 - Surge protection 10KV

Notes

1. MTO Length between 42"-30"
2. Standard color temperature.
3. Standard finish.
4. RAL number required.

T889LED

NOBLE LED BOLLARD

DIMENSIONS

