

TPR WESTFLEX® COVEMAX® X 5.0



FL-SMD-CMX-5.0-WP

Description:

The **Covemax® X 5.0** is a flexible 12VDC tape light for Architectural or Entertainment use. It is available in Non-Protected, Indoor Protected and IP67 rated Outdoor Protection jackets. Westflex® Covemax® X 5.0 is cuttable every 2". There are a range of mounting options available. In addition there is an assortment of extruded housings available for this product. Covemax® X 5.0 is available in four standard color temperatures. This is an extremely versatile product that is usable in a multitude of applications.

Specifications:

- 5 Watts per linear foot
- 20' max run length with feeds from both ends
- 70% Light Maintenance @ 45,000hrs
- Dimmable

- Viewing Angle 120 degrees
- Available in IP67
- 18 Nichia LED's per foot
- Max Lead Length 35' with #20AWG

LUMEN INFORMATION:
 2700K – 569lm/ft
 3000K – 587lm/ft
 4000K – 592lm/ft
 5000K – 623lm/ft

*Also available in 2200K,
 3500K, 4500K, 5700K, 6500K
 Special order – 275' minimum*

Certifications:



Ordering Logic:

MODEL	COLOR	RATING	MOUNTING	LEAD
FL-SMD-CMX-5.0	– 2700 3000 4000 5000	– NP (No Protection) – IP (Indoor Protection) – WP (IP67)	– MC (Adhesive Clip) – MCIP (Screw Clip) – MT (Mounting Track) – MTB (Mounting Track Black)	– T0 (Field Soldered lead) – TC (19.5" Clip-on lead) – T1 (12" Factory Installed lead) – T_ (Factory lead, specify length)

Specifications are subject to change without notice.