



The TPR SHADOW BAR II is an energy efficient LED Linear cove product for Hospitality, Retail, Commercial and Residential use. It has extremely close binning, comes in several color temperatures and is fully dimmable. The Shadow Bar II has an extruded aluminum housing and is rated IP44 for indoor use.

## **Specifications:** \*\*

Construction: **Extruded Aluminum Power Consumption:** SHDW-18-80:

5.76 watts per ft., 306 lumens per ft., 53.125 lumens per watt Silver Color: SHDW-12-150:

**Lumen Output:** 576 lm./ft. 7.2 watts per ft., 384 lumens per ft., 53.333 lumens per watt

SHDW-18-150: 12/18 Nichia High Power/ft. LEDs:

10.8 watts per ft., 576 lumens per ft., 53.333 lumens per watt Input Voltage: 12VDC Weight:

120 Degrees Beam Angle: **Dimensions:** 

12"L x 1 1/8" W x 1"H Lumen Maintenance is 85% at 50,000 hrs.

**Environment:** Indoor Only Listings: ETL / CE / RoHS

IP44 Ratings:

## **Certifications:**







## **Ordering Logic:**

MODEL	AVAILABLE COLOR TEMPERATURES	ACCESSORIES
TPR-SHDW-18-80-DC	2700K	TPR-SHDW-PC12 – 12" POWER CABLE
	3000K*	TPR-SHDW-PC10 – 10 FT. POWER CABLE
TPR-SHDW-12-150-DC	3300K	TPR-SHDW-MC – MOUNTING CLIP
	3900K*	TPR-SHDW-HWA – HARD-WIRED ADAPTER
TPR-SHDW-18-150-DC	4500K	TPR-SHDW-J3 – 3" JUMPER
		TPR-SHDW-J12 – 12" JUMPER

\*Special order \*\* Specifications subject to change without notice.