


# **TPR WESTFLEX® SMD RGB**



## Specifications:\*

- 4.3 watts/linear foot
- 10' Maximum run length \*\*
- Cuttable increments 2" (3 LEDs)
- Approx 70% light output at 25,000 hrs
- 50,000+ hrs expected life
- Color changing


- Voltage: 12V DC
- LED spacing: 18 LEDs per foot
- Viewing angle: 120 degree
- Turning radius: 1" along the
  - vertical plane
- Available for Indoor/Outdoor (IP67)




### **Product Information:**

| Color Options      | Approximate output for 18" section                     |  |  |  |  |
|--------------------|--|--|--|--|--|
| RGB                | Full On 100 lm   |  |  |  |  |
|                    | Red Only 28 lm   |  |  |  |  |
|                    | Green Only 55 lm                                       |  |  |  |  |
|                    | Blue Only 17 lm  |  |  |  |  |
| Dimensions         | 0.225"h x 0.625"w w/Clip & Connector                   |  |  |  |  |
| LED Type           | Three Color/Surface Mounted Diode                      |  |  |  |  |
| Mounting           | MS – 3M Self Adhesive (Usable with NP version only)    |  |  |  |  |
|                    | MC – Adhesive Mounting Clip                            |  |  |  |  |
|                    | MCIP – Screw Mounting Clip                             |  |  |  |  |
|                    | MT(B) – Aluminum Track Silver (or Black)               |  |  |  |  |
| Shortest Segment   | 2" (3 LEDs)  |  |  |  |  |
| Max Lead Length    | 20' with #20AWG  |  |  |  |  |
| Shipping Lengths   | 20'-0" roll and field cut to length in 2" increments   |  |  |  |  |
|                    | Pre-cut to length by factory also available            |  |  |  |  |
| Connection Methods | T0 – Field Soldered Tail (Standard)                    |  |  |  |  |
|                    | TC – 19" Clip-on lead                                  |  |  |  |  |
|                    | T1 – 12" Factory installed lead (Standard)             |  |  |  |  |
|                    | T – Factory installed lead cut to custom length        |  |  |  |  |
| Listing & Standard | ETL Class 2 – UL 2108 (LV Lighting) IP67 on WP version |  |  |  |  |
| Warranty           | Contact Factory for Warranty and Terms of Sale         |  |  |  |  |

#### Westflex FL-SMD-WP-MC-IP Mounting Clip



#### **Westflex FL-SMD MT Mounting Track**







## **Ordering Logic:**

| TYPE         | COLOR                | RATING  | MOUNTING   | LENGTH                                   | LEAD  |
|--------------|----------------------|---|--|--|---|
| TPR-FL-SMD - | – RGB –              | WP –  | MT –   | 10' —                                    | T1  |
| TPR-FL-SMD   | RGB (color changing) | NP - No Protection added IP - Indoor Protected WP - Weatherproof (IP67**) | MS - Self Adhesive (NP only) MC - Adhesive Mounting Clip MCIP - Screw Mounting Clip MT - Aluminum Track Silver | Cut to<br>lengths<br>in 2"<br>increments | T0 - Field Soldered Tail (Standard) TC - 19.5" clip-on lead T1 - 12" Factory installed lead T - Factrory lead custom length |
|              |                      | **Must specify tail length<br>for IP67 rating                             | MTB - Aluminum Track Black   |  |   |
| Rev.9.10a    |                      |   |  |  |   |

<sup>\*</sup>Specifications subject to change without notice.
\*\*Note: For optimum uniformity, refer to factory for recommended run lengths.