



Job Name:	
Job Location:	

Quote:

Client Name:

Quote Date:

43827 Division St. Lancaster, CA 93535 Toll Free: (844) 770-AVPL Fax: (661) 945-2764 sales@avpltg.com www.avpltg.com

AV POLES & LIGHTING

AVA POST TOP ARM

Туре:



32" 16" 4.75" 4.75" UMM Detail

DESCRIPTION

This versatile arm is suited for traditional and contemporary fixtures. The AVA-PT arm is ideal for courtyards, pathways, municipal, and commercial decorative light pole applications.

FEATURES

Decorative cast aluminum and extruded aluminum pole or wall bracket mounting.

Mounts to 23/8" or 27/8" O.D. tenon.

Extruded aluminum, Schedule 40 wall thickness.

6061 alloy T-6 temper with cast aluminum slip fitter.

Available with CB (Center Straight Bar) or CS (Center Scroll Bar).

Stainless steel hardware.

TGIC thermoset polyester powder coat finish is electrostatically applied at a 3.0 mil nominal thickness. A five stage metal pre-treatment process and sealer provide maximum corrosion resistance. The powder top coat is baked in excess of 400 degrees for supreme endurance.





ORDERING INFORMATION

AVPL - _____ - ____ - ____ - ____

ARM	MOUNTING	FINISH
AVA-PT	1-90 🕞	DARK BRONZE
	2-90	BLACK
	2-180 👓	WHITE
	3-90	GREY
	3-120	GREEN
	4-90	
	5-90	
	WALL MOUNT	
	CONTACT FACTORY FOR DRILLING OPTIONS	ALL RAL COLORS AVAILABLE