# THE PERFECT COLOR TEMPERATURE EVERY TIME

This Mini LED Wall Pack is a versatile lighting solution designed to meet your specific needs. With its CCT Selectable feature, you can easily adjust the color temperature to achieve the perfect lighting ambiance for any outdoor application. The included photocell ensures energy savings by automatically turning off the fixture during daylight hours. If desired, you can bypass or disable the photocell using the convenient on/off switch. It also features a frosted lens, providing comfortable illumination and reducing glare. Whether you prefer a j-box installation or a non-j-box installation, our Mini LED Wall Pack offers hassle-free setup for any space. UL Listed and includes a 3-year limited warranty.



C-LI

## **PRODUCT SPECIFICATIONS**

### OVERVIEW

- Initial Delivered Lumens: up to 3600 Lumens
- CRI: ≥ 80
- Field selectable CCT options: 3000K (3125 Lumens), 4000K (3600 Lumens) or 5000K (3400 Lumens)
- Mounting height: 0-15 feet
- Input Power: 24W
- Dimmable: 0-10V dimming to 10%, dims to off

- Operating Temperature Range: -40°F to 104°F (-40°C to 40°C)
- Estimated  $L_{70}$  Lifetime @ 25°C: > 100,000 hours
- Power Factor: > 0.9 at full load
- Total Harmonic Distortion: < 20% at full load
- Limited Warranty: 3 Years\*
- Replaces 100W PSMH
- cULus Listed

FEATURES	RECOMMENDED USE	INPUT VOLTAGE
Color temperature tunable for the perfect color light for your application	• Commercial	• Universal (120V through 277V Operation)
• Photocell for easy energy savings, light will automatically go off during the day	• Entryways	
On/Off switch for photocell if you want to bypass/disable the photocell	• General purpose	
Frosted lens for comfortable glare reducing optical distribution	• Security	
Easy install with or without a j-box	• Residential	
• FCC Part 15, Subpart B, Class A limits for conducted and radiated emissions		

### **ORDERING INFORMATION**

Example SKU: C-WM-A-MWP-3L-SCCT-UL-BZ

C-WM	A	MWP	3L	SCCT	UL	BZ
PRODUCT	SERIES	STYLE	LUMEN PACKAGE	FIELD SELECTABLE CCT	VOLTAGE	HOUSING COLOR
C-WM	A	<b>MWP</b> Mini Wall Pack	<b>3L</b> 3600 (24W)	SCCT Warm White (3000K) Neutral White (4000K*) Cool White (5000K)	<b>UL</b> Universal 120V through 277V operation	<b>BZ</b> Bronze

\*Factory settings are set to 4000K.

#### **CERTIFICATIONS**:



# **C-WM-A-MWP Series**

### **SERIES OVERVIEW**

DIMENSIONS	PRODUCT WEIGHT	MOUNTING HEIGHT
8-1/2" L x 6-3/4" W x 3" D	1.56 lbs.	0-15 feet

### FIXTURE SPECIFICATIONS

HOUSING	Bronze, high impact resistant, polycarbonate housing with diffused frosted lens for glare reduction		
LENS ASSEMBLY	High impact polycarbonate diffused lens		
MOUNTING	Will mount to either a j-box or can be mounted using surface conduit		

### **ELECTRICAL PERFORMANCE**

OPERATING TEMPERATURE RANGE	ESTIMATED L <sub>70</sub> LIFETIME @ 25°C (77°F)	POWER FACTOR	TOTAL HARMONIC Distortion
-40°F to 104°F (-40°C to 40°C)	>100,000 Hours	> 0.9 at full load	< 20% at full load

		INITIAL DELIVERED LUMENS BUG RATING		BUG RATINGS*	SYSTEM	CURRENT DRAW (AMPS)				
SKU	REPLACES	3000K	4000K	5000K	(ALL CCTS)	WATTS	120V	208V	240V	277V
C-WM-A-MWP-3L-SCCT-UL-BZ	100W PSMH	3125	3600	3400	B1-U3-G2	24W	0.196A	0.113A	0.098A	0.085A

\* For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf. Valid with no tilt.

# WARRANTY AND CERTIFICATIONS

WARRANTY	cULus LISTED	DLC	DIMMABLE
3 Year Limited*	Wet Locations	_	0-10V dimming to 10%, dims to off



© 2023 Cree Lighting, A company of IDEAL INDUSTRIES. All rights reserved. For informational purposes only. Content is subject to change. Patent www.creelighting.com/patents. C-Lite and the C-Lite logo are registered trademarks of Cree Lighting, Due to continuous product improvement, information in this document is subject to change. The cULus logo is a registered trademark of UL LLC.

