

# C-STRIP-B-SCCT Series

Linear LED Strip Light with Field Selectable CCT and Wattage

Replaces up to 2-lamp 54W T5HO



## THREE FIXTURES; ONE LINEAR STRIP

Select your savings with our cULus Listed LED Linear Strip Lights in 2-, 4-, and 8-foot lengths. Achieve your desired performance with field switchable CCTs from 3000K, 4000K, or 5000K; and select your wattage, with up to 3 lumen outputs. Each comes with a 5-year limited warranty, and a variety of available accessories.

## PRODUCT SPECIFICATIONS

### OVERVIEW

- Max. Delivered Lumens: 2635 (**S26L**); 5650 (**S56L**); 8845 (**S88L**)
- CRI:  $\geq 80$
- CCT: Selectable 3000K/4000K/5000K
- Input Power: 20W (**S26L**); 15W/30W/45W (**S56L**); 32W/48W/64W (**S88L**)
- Dimmable: 0-10V to 10%
- Operating Temperature Range:
  - (2ft. & 4ft. w/out EB): -40°F to 113°F (-40°C to 45°C)
  - (4ft. w/EB): 32°F to 113°F (0°C to 45°C)
  - (8 ft. w/out EB): -40°F to 104°F (-40°C to 40°C)
  - (8 ft. w/EB): 32°F to 104°F (0°C to 40°C)
- Estimated L<sub>70</sub> Lifetime @ 25°C (77°F): >100,000 hours
- Limited Warranty: 5-Years\*
- Replaces: 2 x F17T8 (**S26L**); 1 x F54T5HO (**S56L**); 2 x F54T5HO (**S88L**)

FEATURES	RECOMMENDED USE	INPUT VOLTAGE
<ul style="list-style-type: none"><li>• FCC Part 15, Subpart B, Class A limits for conducted and radiated emissions</li><li>• Field selectable color temp and light output</li><li>• Integrated 90-minute emergency driver option available</li><li>• Surge protection comes standard: 2kV (2-foot and 8-foot), 4kV (4-foot)</li></ul>	<ul style="list-style-type: none"><li>• Industrial</li><li>• Commercial</li><li>• Offices</li><li>• Retail</li><li>• Residential</li><li>• Manufacturing</li></ul>	<ul style="list-style-type: none"><li>• Universal (120-277V Operation)</li></ul>

### CERTIFICATIONS:

CA RESIDENTS WARNING: Cancer and Reproductive Harm – [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov)



# C-STRIP-B-SCCT SERIES


## ORDERING INFORMATION

Example SKU: C-STRIP-B-LIN4-S56L-SCCT-UL-WH-EB


C-STRIP	B			SCCT	UL	WH	
PRODUCT	SERIES	STYLE	LUMEN PACKAGE	SELECTABLE CCT'S	VOLTAGE	HOUSING COLOR	EMERGENCY BACKUP OPTION
C-STRIP	B	<b>LIN2</b> 2-foot	<b>S26L</b> 2630 Lumens (20W)*	SCCT 3000K, 4000K, 5000K	UL Universal 120-277V Operation	WH White	<b>[blank]</b> w/o Emergency backup option  <b>EB</b> Emergency Battery Back Up - Provides 4W (4') or 8W (8') of power and 90 minutes of emergency operation - Available only with 4' and 8' luminaires
		<b>LIN4</b> 4-foot	<b>S56L</b> 2950 Lumens (22W)* 4420 Lumens (33W)* 5650 Lumens (45W)*				
		<b>LIN8</b> 8-foot	<b>S88L</b> 4520 Lumens (33W)* 6850 Lumens (50W)* 8840 Lumens (64W)*				

\*Lumen values are measured at 4000K.


## S26L



## S56L



## S88L



## SERIES OVERVIEW

DIMENSIONS	PRODUCT WEIGHT	MOUNTING HEIGHT	SPACING
<b>(S26L):</b> 24-1/8" L x 3" W x 2-5/8" H	2.05 lbs.	10-15 feet	End to end, or 1 to 1-1/2 times the mounting height
<b>(S56L):</b> 48" L x 3" W x 2-5/8" H	3.76 lbs., (w/o EB) 4.12 lbs. (w/EB)		
<b>(S88L):</b> 96" L x 3" W x 2-5/8" H	8.02 lbs., (w/o EB) 8.38 lbs. (w/EB)		

# C-STRIP-B-SCCT SERIES

## FIXTURE SPECIFICATIONS

<b>HOUSING</b>	High quality steel with white polyester powder coat finish. 3mil thickness for superior corrosion resistance and maximum environmental durability
<b>LENS ASSEMBLY</b>	Frosted polycarbonate diffuser lens for superior light uniformity and glare reduction
<b>MOUNTING</b>	Keyhole slots for surface mounting or suspended mounting using hook and chain (sold separately)

## LUMINAIRE AND ELECTRICAL PERFORMANCE

OPERATING TEMPERATURE RANGE	ESTIMATED L <sub>70</sub> LIFETIME @ 25°C (77°F)	POWER FACTOR	TOTAL HARMONIC DISTORTION
<b>(2ft. &amp; 4ft. w/out EB):</b> -40°F to 113°F (-40°C to 45°C) <b>(4ft. w/EB):</b> 32°F to 113°F (0°C to 45°C) <b>(8 ft. w/out EB):</b> -40°F to 104°F (-40°C to 40°C) <b>(8 ft. w/EB):</b> 32°F to 104°F (0°C to 40°C)	>100,000 Hours	>.9	<20%






SKU	REPLACES	LUMEN OUTPUT	SYSTEM WATTS	CURRENT DRAW (AMPS)			
				120V	208V	240V	277V
C-STRIP-B-LIN2-S26L-SCCT-UL-WH	2-Lamp F17T8	2600L	20W	0.160	0.092	0.080	0.069
C-STRIP-B-LIN4-S56L-SCCT-UL-WH	1-lamp T5HO	5600L	15W/30W/45W	0.351	0.202	0.175	0.152
C-STRIP-B-LIN4-S56L-SCCT-UL-WH-EB							
C-STRIP-B-LIN8-S88L-SCCT-UL-WH	2-lamp T5HO	8800L	32W/48W/64W	0.544	0.314	0.272	0.235
C-STRIP-B-LIN8-S88L-SCCT-UL-WH-EB							

## WARRANTY AND CERTIFICATIONS

WARRANTY	cULus LISTED	DLC
5-Year-Limited*	Damp Locations	5.1 Standard

# C-STRIP-B-SCCT SERIES

## ACCESSORIES

	<p><b>PIR MOTION SENSOR   120-277V</b></p> <p><b>SKU:</b> C-ACC-B-PIR-UL  <b>USE:</b> Contains two lenses; recommended mounting heights: low bay (8-25 feet), high bay (20-40 feet). Mounts to side knock out on fixture.</p>
	<p><b>MICROWAVE MOTION SENSOR   120-277V</b></p> <p><b>SKU:</b> C-ACC-MW-L  <b>USE:</b> Microwave motion sensor, recommended for 8'-20' mounting heights. Adjustable dip switches for time delays, and step dimming controls. 120-277V. For use with C-STRIP-B and C-WR-B Series.</p>
	<p><b>SUSPENSION MOUNTING KIT</b></p> <p><b>SKU:</b> C-STRIP-A-SK  <b>USE:</b> Hook and chain mounting kit for suspended applications, contains two 30-inch chains with hooks. For use with C-STRIP-B.</p>
	<p><b>WIRE GUARD   2-FOOT</b></p> <p><b>SKU:</b> C-STRIP-A-WG2  <b>USE:</b> White, powder-coated steel 2-foot wire guard provides added durability for more demanding applications. For use with C-STRIP-B Series.</p>
	<p><b>WIRE GUARD   4-FOOT</b></p> <p><b>SKU:</b> C-STRIP-A-WG4  <b>USE:</b> White, powder-coated steel 4-foot wire guard provides added durability for more demanding applications. For use with C-STRIP-B Series.  <b>Note:</b> When using with C-STRIP-B-LIN8 Series, (2) 4-foot wire guards are required.</p>

© 2023 Cree Lighting, A company of IDEAL INDUSTRIES. All rights reserved. For informational purposes only. Content is subject to change. Patent [www.creelighting.com/patents](http://www.creelighting.com/patents). C-Lite and the C-Lite logo are registered trademarks of Cree Lighting. The cULus logo is a registered trademark of UL LLC. The DLC QPL logo and the DLC QPL Premium logo are registered trademarks of Northeast Efficiency Partnerships, Inc.

**US: [creelighting.com](http://creelighting.com), [e-conolight.com](http://e-conolight.com)      Distribution/Sales: 855-617-2733 | Customer Service: 888-243-9445**

Rev. Date: V4 08/30/2023

For informational purposes only. Content is subject to change. \*See [lighting.cree.com/warranty](http://lighting.cree.com/warranty) for details

**C-LITE**  
LED LIGHTING