

ATF7509-DTW





| Job Information | | |
|-----------------|--|--|
| Project Name | | |
| Туре | | |
| Location | | |
| Quantity | | |
| Date | | |

8.5W Dim-To-Warm LED Track Head

Track Lighting

Description

The ATF7509-DTW is a dim-to-warm 8.5W high powered LED track fixture specially designed for task and accent lighting. Available in black and white finishes.

Features

Body

Constructed of aluminum, the body features an aesthetically pleasing smooth cylindrical shape. The body included a colour matching aluminum heat sink in order to provide maximum heat dissipation.

Beam Spread

The fixture is available in 15°, 38° and 60° beam angle.

Dimming

The integrated driver is dims the light to a warmer colour temperature when used with TRIAC / ELV dimming controls (Consult factory for compatible

dimmers).

Adjustability

Adjustable up to 90° tilt and 330° rotation to allow for spotlight into multiple directions.

LED Characteristics

High powered 8.5W Sharp® GW6NGWJCS0C LED chip maintains uniform intensity with a typical luminous flux up to 532 lumens, making it a suitable replacement for 50W PAR20 halogen lamps; with a CRI of 90. Available in 2750°K (dimmable to 2000°K) correlated colour temperature.

Compatibility

Fixture is provided with A-Line connector which is compatible with Juno style track. For other connector configuration (Liteline, Halo), please contact your A-Line representative.


QuickShip In-Stock

In-Stock products ship within two business days of an order being released.*



| SPECIFICATION | | | | |
|-------------------|------------------|--|--|--|
| Application | Track | | | |
| Approved Location | Dry / Indoor | | | |
| Beam Angle | 15° / 38° / 60° | | | |
| CCT | 2750 K~2000 K | | | |
| Certification | cETLus | | | |
| Colour | BK / WH | | | |
| CRI | 90 | | | |
| Dimming | Yes | | | |
| Dimming Tech | TRIAC, ELV | | | |
| _M79 | Yes | | | |
| umen Maintenance | 70% @ 50,000 Hrs | | | |
| umens | 532 | | | |
| umens per Watt | 62.6 | | | |
| Primary Voltage | 120V AC | | | |
| Rated Life | 35,000 hrs | | | |
| Rotation | 330° | | | |
| Γilt | 90° | | | |
| Warranty | 5 Years | | | |
| Nattage | 8.5 | | | |
| | | | | |

Technical Drawings



Ordering Guide

denotes QuickShip



* QuickShip option is available on orders of 100 pieces or less. QuickShip lead time may vary for orders greater than 100 pieces. No additional shipment rates apply. Subject to availability.

**Notes:* For additional options please consult your A-Line Lighting representative. Juno is a registered trademark of Juno Lighting Group. Halo is a registered trademark of Cooper Lighting. Due to our continued efforts to improve our products, product specifications are subject to change without notice.

Liteline Corporation Copyright © 2019 All rights reserved. Telephone 416.996.1856 1.866.730.7704 Fax 905.709.5255 1.888.738.9736



Photometry

ATF7509-DTW-38: 8.5W, Dim-To-Warm LED Track, 2750 K, 38° Beam Angle

Zonal Lumen Summary

| Zone | Lumens | % Luminaire |
|-------|--------|-------------|
| 0-30 | 408.2 | 76.7% |
| 0-40 | 476.3 | 89.5% |
| 0-60 | 520.0 | 97.7% |
| 60-90 | 12.4 | 2.3% |
| 0-90 | 532.4 | 100% |
| | | |

