

## LEDBAR-CCT

LED Fluorobar, 290-1850 Lumens, 5-22W, Colour Selectable  
Cove, Under Cabinet & Millwork

Job Information		
Project Name		Type
Location		
Quantity		Date
Contact/Phone		
Notes		

### Features

#### Housing

Durable extruded aluminum frame with frosted smooth lens. Suitable for dry location applications only. On-body ON/OFF switch and a 5-position 2700-5000K CCT select switch are provided for individual control..

#### LED Driver

Fixture is provided with built-in silent non-flicker electronic LED driver, 120V, 50 / 60Hz.

#### Light Output

Providing up to 1850 lumens, and up to 96lm/W, this undercabinet fixture also features a 5-position 2700-5000K CCT select switch.

#### Dimming

Fixture is 100~0% dimmable with industry standard TRIAC and ELV dimmers.

#### LED Characteristics

Powered by LED integrated strip that maintains uniform intensity with 70%

lumens at 60,000 hours with a rated life of 36,000 hours average life; at 90 CRI.

#### Beam Spread

The fixture lens provides for 125° beam spread.

#### Linking

Complete with a joiner, these no shadow linking fixtures can be linked up to 2500 mA / 300 W.

#### Mounting Kit

Hardware provided for mounting fixture to standard horizontal surfaces or vertical wall surface.


#### Operating Temperature

-18°C~-40°C (0°F~-104°F).

#### Rating


Suitable for use in closets. Compliant with NFPA 70, NEC section 410.16 (A)(1). Maintain a minimum of 6" clearance to combustible materials at all times.

SPECIFICATION	
Approved Location	Dry
Beam Angle	125°
CCT	2700 K / 3000 K / 3500 K / 4000 K / 5000 K
Certification	cULus
Connection Type	3-Wire
CRI	90+
Dimming	Yes
Dimming Technology	TRIAC / ELV
Lumens	Up to 1850
Lumens per watt	Up to 96
Min. Start Temp.	-18°C
Lumen Maintenance	70% @ 60,000 hrs
Power Factor	>0.95
Rated Life	36,000 hrs
THD	<15
Voltage	120V
Warranty	3 Years
Wattage	Up to 22



### Description

This LED Fluorobar light is a linear light with an integrated LED strip. Available with various lengths featuring ON/OFF and CCT Select switch to meet any installation application.



	LEDBAR14-CCT	LEDBAR23-CCT	LEDBAR34-CCT	LEDBAR46-CCT	LEDBAR58-CCT
Length (L)	13½" 343mm	22½" 574mm	34¾" 874mm	46¾" 1174mm	58" 1474mm
Wattage (W)	5	9	14	18	22
Lumens	2700 K	250	550	850	1000
	3000 K	400	775	1175	1500
	3500 K	350	705	1120	1400
	4000 K	400	775	1175	1500
	5000 K	400	775	1175	1500



### Ordering Guide

LED BAR	Fixture Length	-CCT
	14 : 13½", 5W	
	23 : 22½", 9W	
	34 : 34¾", 14W	
	46 : 46¾", 18W	
	58 : 58", 22W	

#### Notes:

Accessories are sold separately. For additional options consult your Liteline representative.  
Due to our continued efforts to improve our products, product specifications are subject to change without notice.

## Accessories (Power feed required)

### Power Cord

**ALFT6000-WH-3**

6' Flexible 3-wire power cord for FluoroBar series.

**ALFT6000S-WH-3**

6' Flexible 3-wire power cord with on/off switch, for FluoroBar series.

**ALFT6016-WH-3**

16' Flexible 3-wire power cord for FluoroBar series.

### Power Cord with 90° Connector

**ALFT60901-WH-3**

6' Flexible 3-wire power cord with 90° connector (top connection).

**ALFT60902-WH-3**

6' Flexible 3-wire power cord with 90° connector (left connection).

**ALFT60903-WH-3**

6' Flexible 3-wire power cord with 90° connector (bottom connection).

**ALFT60904-WH-3**

6' Flexible 3-wire power cord with 90° connector (right connection).

### Hardwire Box

**ALFT6300-WH**

Hardwire box for FluoroBar series, with on/off switch.

**ALFT6300-OS-WH**

LED BAR hardwire with motion sensor.

### Flexible Cord with 90° Connectors

**ALFT90-WH-3**

6" Flexible 3-wire cord with 90° connectors (top connection).

**ALFT901-WH-3**

6" Flexible 3-wire cord with 90° connectors (left connection).

**ALFT902-WH-3**

6" Flexible 3-wire cord with 90° connectors (bottom connection).

**ALFT903-WH-3**

6" Flexible 3-wire cord with 90° connectors (right connection).

### Flexible Connectors

**FBT6106-WH-3**

6" Flexible 3-wire connector.

**FBT6100-WH-3**

12" Flexible 3-wire connector.

**FBT6124-WH-3**

24" Flexible 3-wire connector

**FBT6136-WH-3**

36" Flexible 3-wire connector

### Clips

**LEDBAR-MAGCLIP-3**

Magnetic mounting clips for LEDBAR, 3-pack.