

AMON MINI



Pathway bollard series. Fixtures consist of:


- Multi-step powder-coat painting process, optimized against UV rays and corrosion.
- Robust copper-free extruded aluminum column profile and copper-free precision die-cast aluminum housing, ring/faceplate, top cap, and inspection access door.
- Extra-clear, flat, tempered silk-screened soda-lime glass diffuser.
- Satin UV-stabilized, high-impact resistant diffuser (SOFT versions).
- Custom molded, anti-aging gasket(s).
- Stainless steel external hardware.
- High-efficiency COB, combined with an optimized passive cooling system, provides a long LED life.
- Internal specular reflector coated with 5-layers of PVD 99.98% pure aluminum providing >95% reflection.
- IESNA Type V light distribution.
- Diffuse light emission (SOFT).

- Input voltage: 120-277 V (50 / 60 Hz), integral 0-10 V dimming driver.
- Integral surge protector can withstand up to 10 kV transient line surge.
- Steel ground base plate included for bollards.
- Consult factory for dimming options, custom finishes (please specify RAL color), and non-cataloged CCT (Kelvin) options.
- Consult factory for custom post height options.
- Base heavy-duty covers, anchor bolts, and direct-burial support available for AMON MINI / MAXI (ordered separately).
- Product meets Buy American Act requirements within ARRA.
- 5-year warranty.
- Marine Grade finish.
- Suitable for Natatorium applications.




FINISHES

- AN-96 / Iron gray / Textured
- BK-81 / Black / Textured
- GR-94 / Aluminum metallic / Textured
- WH-87 / White / Textured
- RB-10 / Iron rust / Textured



AMON
MINI



AMON
MINI SOFT



Scan here
for installation
instructions

Lumen Output	27K	3K	35K	4K	5k
Amon Mini Soft	1293	1314	1335	1357	1378
Amin Mini T5	1932	1963	1994	2025	2056

45W Max Wattage

Order Guide - Amon Mini




Order code example

AMI-47-OPEN-40-AM-3K-120-NA-BC-ANC


AMI-

Bollard Height	Optics	Wattage	Finish	Kelvin	Voltage	Controls	Accessories
35 35 Inch (min)	OPEN Type V	12 12 watt	AM Aluminum Metallic	27K 2700k	UNV 120-277V	NA Non Dimming	BC Base Cover
47 47 Inch	SOFT Type V Diffuse	20 20 watt	IG Iron Gray	3K 3000k			
114 114 Inch (max) (9.5' OAH)		40 40 watt	IR Iron Rust	35K 3500k		ELV ELV Dimming	ANC Template w/ Anchor bolts
XX Specify Height Must be within range		45 45 watt (max)	BK Textured Black	4K 4000k			
		XX Specify Wattage Must be below max	WH Textured White	5K 5000k			DB Direct Burial
			CC Custom Color	RED Static Red			HSS House Side Shield
				BLU Static Blue			LOGO Custom Logo
				GRN Static Green			PHC1 120V Photocell
				AMB Amber			OCC1 on/off Occupancy Sensor
							OCC2 hi/lo Occupancy Sensor


OPTIONAL ACCESSORIES



Base Cover



Anchor Bolts w/ template



Direct Burial Base



AMON MINI fixture on a
MAXI post. Overall height
is 9.5-feet
(1' fixture; 8.5' post).

Performance in Lighting reserves the right to make all necessary changes without prior notice.

Performance in Lighting - 2621 Keys Pointe - Conyers, Georgia 30013 - USA - voice 770.822.2115 - info.usa@pil.lighting
www.performanceinlighting.com

Revision 04
04/23