

# BLIZ ROUND



Ceiling and wall mount series. Fixtures consist of:

- Multi-step powder-coat painting process, optimized against UV rays and corrosion.
- Copper-free precision die-cast aluminum housing and ring/faceplate.
- High transmittance, internally coated, soda-lime pressed glass diffuser, thermally and chemically quenched to strengthen the impact resistance and reduce the effect of rapid temperature changes.
- Custom molded, anti-aging gasket(s).
- Stainless steel external hardware.
- Custom MCPCB utilized to maximize heat dissipation and promote a long LED life.
- 100% uniform diffused light emission.
- Input voltage: 120-277 V (50 / 60 Hz), integral 0-10 V dimming driver.


- Optional, integral, high-frequency motion-sensor operating at a frequency of 5.8 GHz +/- 75 MHz (HF versions).
- Optional, integral, emergency battery-pack designed for a minimum operation of 90 minutes (EMPK versions).
- Consult factory for dimming options, custom finishes, and non-cataloged CCT (Kelvin) options.
- Product meets Buy American Act requirements within ARRA.
- 5-year warranty on components.
- 10-year warranty on glass.
- Marine Grade finish.
- Suitable for Natatorium applications.



## FINISHES


- AN-96 / Iron gray / Textured
- GR-94 / Aluminum metallic / Textured
- WH-87 / White / Textured
- BK-81 / Black / Textured
- RB-10 / Iron rust / Textured

12"



BLIZ ROUND  
30

16"



BLIZ ROUND  
40

Scan here  
for installation  
instructions



Lumen Output	27K	3K	35K	4K	6K
<b>Bliz Round 30</b>	2096	2178	2260	2343	2425
<b>Bliz Round 30 EMPK</b>	2096	2178	2260	2343	2425
<b>Bliz Round 30 HF</b>	2096	2178	2260	2343	2425
<b>Bliz Round 40</b>	2652	2739	2826	2912	2999
<b>Bliz Round 40 EMPK</b>	2652	2739	2826	2912	2999
<b>Bliz Round 40 HF</b>	2652	2739	2826	2912	2999

30W/40W Max Wattage

Revision 07  
07/23

# TRIM OPTIONS Contact Factory for MOQ- Some options may require reduced wattage




**STANDARD TRIM**



**EYELID TRIM**



**CROSS TRIM**



**VISA TRIM**

## Order Guide - Bliz Round

Order code example

BRD-30-AM-3K-277-NA-H/L-STANDARD

BRD-

Housing Style	Wattage	Finish	Color Temperature	Voltage	Controls	Accessories	Optional Trim
30 Round 12"	20 20 watt	AM Aluminum Metallic	27K 2700k	UNV 120-277V	NA Non Dimming	EMPK Emergency Battery back up	(See pictures above) Contact Factory for MOQ <b>Standard Trim</b>
40 Round 16"	30 30 watt (Bliz 30 MAX)	IG Iron Gray	3K 3000k		0-10V 0-10V Dimming	CWEMPK Cold Weather Emergency Battery back up (-4°F - 122°F)	<b>Eyelid Trim</b>
		IR Iron Rust	35K 3500k		ELV ELV Dimming		<b>Cross Trim</b>
		BK Textured Black	4K 4000k		1% 1% Dimming		<b>Visa Trim</b>
		WH Textured White					<b>CON</b> 1/2" Conduit Adapter
	XX Specify Wattage must be below max	CC Custom Color				<b>HF</b> High Frequency Occupancy Sensor w/ daylight PHC	<b>TP</b> Tamper Proof hardware