

# GUELL ZERO



Economical low-profile landscape flood light series.

Fixtures consist of:


- Multi-step powder-coat painting process, optimized against UV rays and corrosion.
- Copper-free precision die-cast aluminum housing, ring/faceplate, and adjustable mounting arm.
- Extra-clear, flat, tempered silk-screened soda-lime glass diffuser.
- Custom molded, anti-aging gasket(s).
- High-efficiency COB, combined with an optimized passive cooling system, provides a long LED life.

- NEMA 6H x 5V light distribution (S/W).
- Input voltage: 120-277 V (50 / 60 Hz), integral 1-10 V dimming driver.
- Pre-wired factory sealed cable for external electrical connection included.
- Standard robust 1/2" NPS knuckle mount with 180° adjustable swivel arm (SA versions) and rugged, locking teeth for a simplified installation.
- 5-year warranty.
- Marine Grade finish.
- Suitable for Natatorium applications.



## FINISHES

- GR-94 / Aluminum metallic / Textured
- RB-10 / Iron rust / Textured
- BK-81 / Black / Textured
- AN-96 / Iron gray / Textured
- WH-87 / White / Textured



GUELL  
ZERO

Lumen Output	3K	4K
<b>Guell+Zero 13W</b>	<b>1249</b>	<b>1549</b>
<b>Guell+Zero 26W</b>	<b>2569</b>	<b>2769</b>

Scan here  
for installation  
instructions



# Order Guide - Guell Zero



Order code example

GZERO-26-AM-3K-120

**GZERO-**

Wattage	Finish	Color Temperature	Voltage	Controls	Accessories
13 13 watt	<b>AM</b> Aluminum Metallic	<b>27K</b> 2700K	<b>UNV</b> 120-277V	<b>NA</b> Non Dimming	
<b>26</b> 26 watt (max)	<b>IG</b> Iron Gray	<b>3K</b> 3000k		<b>0-10V</b> 0-10V Dimming	
<b>XX</b> Specify wattage must be below max	<b>IR</b> Iron Rust	<b>35K</b> 3500K			
	<b>BK</b> Textured Black	<b>4K</b> 4000k			
	<b>WH</b> Textured White	<b>6K</b> 6000K			
	<b>CC</b> Custom Color	<b>AMB</b> Amber			
		<b>BLU</b> Static Blue			
		<b>RED</b> Static Red			
		<b>GRN</b> Static Green			