

KHA SLIM 250



Slim area and site lighting series. Fixtures consist of:

- Multi-step powder-coat painting process, optimized against UV rays and corrosion.
- Copper-free aluminum extruded post.
- Copper-free precision die-cast aluminum housing and top cap.
- Corrosion-resistant AISI 316 stainless steel post and top cap.
- Satin UV-stabilized diffuser.
- Custom molded, anti-aging gasket(s).
- Stainless steel external hardware.
- Custom MCPCB utilized to maximize heat dissipation and promote long LED life.
- Diffuse light emission.
- IESNA Type V light distribution.
- Input voltage: 120-277V (50 / 60 Hz), integral driver.

- Anchor bolts available for bollards (ordered separately).
- Suitable for most coastal applications (stainless steel versions).
- Five optional finishes available. Add finish suffix to any part number for textured Black (BK-81), Iron gray (AN-96), Aluminum metallic (GR-94), White (WH-87), Iron rust (RB-10) when not standard.
- Consult factory for dimming options, marine-grade, custom finishes (please specify RAL color), and non-cataloged CCT (Kelvin) options including static colors.
- Consult factory for custom post height options.
- Product meets Buy American Act requirements within ARRA.
- 5-year warranty.
- Marine Grade finish.
- Suitable for Natatorium applications.




FINISHES

- AN-96 / Iron gray / Textured
- BK-81 / Black / Textured
- INOX / Stainless steel / Matt
- GR-94 / Aluminum metallic / Textured
- WH-87 / White / Textured
- RB-10 / Iron rust / Textured

Ø39/16" (Ø90mm)

Overall Height
3.16' min
20' max



Diffuser Length
12" min
48" max

Lumen Output	Wattage	4K /80CRI
12" Diffuser	25W max	2595lm
24" Diffuser	50W max	5190lm
48" Diffuser	75W max	7800lm

Contact factory for other CCT's and reduced lumen options



Scan Here for
Installation Instructions

KHA SLIM
250



Order Guide - Kha Slim 250

Order code example

KHA8-XX-24-50-SS-3K-120-NA-DB

KHA8

Overall Column Height	Diffuser Size	Wattage	Finish	Kelvin	Voltage	Controls	Accessories
38 38 inch 12" diffuser min	12 12" diffuser 25W Max	25 25 watt	SS Stainless Steel	27K 2700k	UNV 120-277V	NA Non Dimming	DB Direct Burial
				3K 3000k			
50 50 inch 24" diffuser min	24 24" diffuser 50W Max	40 40 watt	AM Aluminum Metallic	35K 3500k	0-10V 0-10V Dimming	ELV ELV Dimming	BT Bubble Trim
				4K 4000k			DIA Diamond Trim
74 74 inch 48" diffuser min	48 48" diffuser 75W Max	75 75 watt max	IG Iron Gray	5K 5000k	GRN Static Green	ANG Angle Trim	GRL Grill Trim
				4K 4000k			PER Perforated Shield Full
240 240 Inch max height	XX Specify Wattage Must be below max	XX Specify Wattage Must be below max	IR Iron Rust	5K 5000k	AMB Static Amber	4WIN Four Window	PER Perforated House Side Shield
				5K 5000k			PHSS Perforated House Side Shield
XX Specify Height Must be within range	XX Specify Height Must be within range	XX Specify Height Must be within range	BK Textured Black	65K 6500k	RGBW RGBW* Only available with 24" diffuser Contact factory for control details	OCC Occupancy Sensor Not Available with RGBW or with Trim options	RIB Ribbon Trim
				65K 6500k			CC Custom Color
			WH Textured White	RED Static Red			
			BK Textured Black	BLU Static Blue			
			WH Textured White	GRN Static Green			
			CC Custom Color	AMB Static Amber			
				RGBW RGBW* Only available with 24" diffuser Contact factory for control details			

OPTIONAL ACCESSORIES

DESCRIPTION	FINISH	PART NUMBER
-------------	--------	-------------

Controls

Kit driver 48V		17433
Kit driver 48V WP		17096

RF Controls

RGBW RF controller 4 channel (0.4A each CH)		3104174
RGBW RF controller WP 4 channel (0.4A each CH)		31041740
RGBW hand held remote		310429

WiFi Controls

RGBW WiFi controller 4 channel (0.4A each CH)		3104164
RGBW WiFi controller WP 4 channel (0.4A each CH)		31041640


DMX Controls

RGBW DMX enabler/decoder 4 channel (0.4A each CH)		178974
RGBW DMX enabler/decoder WP 4 channel (0.4A each CH)		1789740
Terminating resistor		11015
Terminating resistor WP		110150



App (free) – “EasyLighting”

EasyLighting is an application that uses a WiFi network to control, adjust, and customize the lighting color or CCT, brightness, and the rate of change. With this application you can control EasyLighting products through most mobile devices



17433



17096



**3104174
3104275**



**31041740
31042750
31041640
31042650
1789740
1789750**



310429



310421



**3104164
3104265**



**178974
178975**



11015



110150