

MAGICCLICK OVAL




- Ceiling and wall mount series. Fixtures consist of:
- Multi-step powder-coat painting process, optimized against UV rays and corrosion.
 - Copper-free die-cast aluminum housing, ring, and faceplates.
 - High transmittance, internally coated, soda-lime pressed glass diffuser, thermally and chemically quenched to strengthen the impact resistance and reduce the effect of rapid temperature changes.
 - The ring/faceplate is integral with the diffuser.
 - Custom molded, anti-aging gasket(s).
 - Stainless steel external hardware.

- Custom MCPCB utilized to maximize heat dissipation and promote a long LED life.
- 100% uniform diffused light emission.
- Input voltage: 120-277 V (50 / 60 Hz), integral driver.
- Standard hinge-style housing allows for a simplified installation.
- Consult factory for dimming options, custom finishes (please specify RAL color), and non-cataloged CCT (Kelvin) options.
- Product meets Buy American Act requirements within ARRA.
- 5-year warranty on components.
- 10-year warranty on glass.
- Marine Grade finish.
- Suitable for Natatorium applications.




FINISHES


- AN-96 / Iron gray / Textured
- GR-94 / Aluminum metallic / Textured
- WH-87 / White / Textured
- BK-81 / Black / Textured
- RB-10 / Iron rust / Textured



MAGICCLICK
OVAL



MAGICCLICK
OVAL SHADE H



MAGICCLICK
OVAL SHADE V



Scan Here for
Installation Instructions

Lumen Output	27K	3K	35K	4K	5K
Magclick Oval	575	608	641	675	708
Magclick Oval Shade H	316	334	352	370	388
Magclick Oval Shade V	358	377	395	414	451

11W Max Wattage

Revision 02
10/22

Order Guide - Magiclick Oval



Order code example

MCO-OPEN-11-AM-3K-120-NA

MCO-

--	--	--	--	--	--

Trim Style	Wattage	Finish	Kelvin	Voltage	Controls	Options
OPEN Open Trim	11 11 watt (max)	AM Aluminum Metallic	27K 2700K	UNV 120-277V	NA Non Dimming 0-10V 0-10V Dimming ELV ELV Dimming	REM Remote mounted Emergency battery back-up TP Tamper proof hardware
SH Horizontal Shade	XX Specify wattage must be below max	IG Iron Gray	3K 3000k			
SV Vertical Shade		IR Iron Rust	35K 3500k			
		BK Textured Black	4K 4000k			
		WH Textured White	5K 5000K			
		CC Custom Color	RED Static Red			
			BLU Static Blue			
		GRN Static Green				