


NIKKO+21 LA



Surface-mount doorway and hallway lights and post mount series. Fixtures consist of:


- Multi-step powder-coat painting process, optimized against UV rays and corrosion.
- Copper-free die-cast aluminum housing, ring, and faceplates.
- High transmittance, internally coated, soda-lime pressed glass diffuser, thermally and chemically quenched to strengthen the impact resistance and reduce the effect of rapid temperature changes.
- Custom molded, anti-aging gasket(s).
- Stainless steel external hardware.
- High-efficiency COB, combined with an optimized passive cooling system, provides a long LED life.

- 100% uniform diffused light emission.
- Input voltage: 120-277 V (50 / 60 Hz), integral driver.
- Consult factory for dimming options, custom finishes (please specify RAL color), and non-cataloged CCT (Kelvin) options including static colors.
- Wall bracket and post accessories available (ordered separately).
- Product meets Buy American Act requirements within ARRA.
- 5-year warranty on components.
- 10-year warranty on glass.
- Marine Grade finish.
- Suitable for Natatorium applications.



FINISHES

- AN-96 / Iron gray / Textured
- RB-10 / Iron rust / Textured
- GR-94 / Aluminum metallic / Textured
- WH-87 / White / Textured
- BK-81 / Black / Textured



NIKKO+
21 LA

Lumen Output	27K	3K	35K	4K	5K
Nikko+21 LA	695	712	729	746	763

11W Max Wattage

Scan here
for installation
instructions



Order Guide - Nikko+21 LA




Order code example


N21L-11-AM-4K-120-0-10V-REM

N21L


Light Source	Finish	Kelvin	Voltage	Controls	Accessories
LED 11 watt LED (max) XX Specify Wattage Must be below max INC 60W INC Edison Lamp (Lamp by others)	AM Aluminum Metallic	LED ONLY 27K 2700k	UNV 120-277V	LED ONLY NA Non Dimming	REM Remote Mounted Emergency Battery Back-Up CLEAR Clear Glass INC Version Only WB Wall Bracket P7 7.8" Post P22 22.95" Post P32 32.79" Post
		3K 3000k		0-10V 0-10V Dimming	
	IG Iron Gray	35K 3500k		ELV ELV Dimming	
	IR Iron Rust	4K 4000k			
	BK Textured Black	5K 5000k			
	WH Textured White	65K 6500k			
	CC Custom Color	RED Static Red			
		BLU Static Blue			
		GRN Static Green			




WB
Wall Bracket



P7
7.8" Post



P22
22.95" Post



P32
32.79" Post



CLEAR GLASS
60W INC VERSION

Performance in Lighting reserves the right to make all necessary changes without prior notice.

Performance in Lighting - 2621 Keys Pointe - Conyers, Georgia 30013 - USA - voice 770.822.2115 - info.usa@pil.lighting
www.performanceinlighting.com

Revision 02
10/22