

SPILLO



Area and site lighting series. Fixtures consist of:


- Multi-step powder-coat painting process, optimized against UV rays and corrosion.
- Copper-free precision die-cast aluminum housing and top cap.
- Custom molded, anti-aging gasket(s).
- Stainless steel external hardware.
- Custom MCPCB utilized to maximize heat dissipation and promote a long LED life.
- High-transmittance transparent optics.
- The "Secure Light Distribution" system can bypass individual diodes in the event of a single LED failure to ensure continuous uniform light distribution.
- IESNA Type II light distribution.
- IESNA Type V light distribution.
- Input voltage: 120-277 V (50 / 60 Hz), integral 0-10 V dimming driver.

- Integral surge protector can withstand up to 10 kV transient line surge.
- Pre-wired factory sealed cable for external electrical connection included.
- Consult factory for dimming options, custom finishes (please specify RAL color), and non-cataloged CCT (Kelvin) options.
- Consult factory for custom pre-wired factory sealed cable length options.
- Consult factory for pole information.
- Consult factory for wall bracket accessory, multi-head pole top mounting, and other custom options.
- Ø3" and Ø4" post top adapters, and poles in 8' / 10' / 12' / 14' options available (ordered separately).
- Product meets Buy American Act requirements within ARRA.
- 5-year warranty.
- Marine Grade finish.
- Suitable for Natatorium applications.



FINISHES

- AN-96 / Iron gray / Textured
- BK-81 / Black / Textured
- GR-94 / Aluminum metallic / Textured
- WH-87 / White / Textured
- RB-10 / Iron rust / Textured



SPILLO

Scan here
for installation
instructions



Lumen Output	3K	4K
Spillo T5	4052	4357
Spillo T2	4177	4492

65W Max Wattage

Revision 03
02/23

Order Guide - Spillo



Order code example

SPILLO-T2-65-AM-3K-120-NA-4"/P8

SPILLO-

--	--	--	--	--	--	--

Light Output	Wattage	Finish	Kelvin	Voltage	Controls	Accessories
T2 Type II	65 65 watt (max)	AM Aluminum Metallic	27K 2700K	UNV 120-277V	NA Non Dimming	4" 4" Pole top adapter
T5 Type V	XX Specify Wattage Must be below max	IG Iron Gray	3K 3000k		0-10V 0-10V Dimming	3" 3" Pole top adapter
		IR Iron Rust	35K 3500K		ELV ELV Dimming	P8 8' Pole (4")
		BK Textured Black	4K 4000k			P10 10' Pole (4")
		WH Textured White				P12 12' Pole (4")
		CC Custom Color				P14 14' Pole (4")
						P16 16' Pole (4")
						P18 18' Pole (4")
						PXX Specify Pole height
						GFCI GFCI outlet
						Consult factory for more options

Revision 03
02/23

SPILLO




90013
Adapter pole top 3"




90014
Adapter pole top 4"


POLES




71408
Pole 8' (4" diameter)




71410
Pole 10' (4" diameter)




71412
Pole 12' (4" diameter)



71414
Pole 14' (4" diameter)



71416
Pole 16' (4" diameter)



71418
Pole 18' (4" diameter)

POLE DETAILS:

Pole - The pole shaft is extruded from seamless alloy aluminum.

Handhole - A covered handhole with hardware and grounding provision are provided.

Anchor Base - The anchor base is cast from 356 alloy aluminum. The completed assembly is heat-treated to a T6 temper. Aluminum nut covers are included with anchor base unless otherwise specified.

Anchor Bolts - Anchor bolts conform to ASTM F1554 Grade 55 and are provided with two hex nuts and two flat washers. Bolts have an "L" bend on one end and are galvanized a minimum of 12" on the threaded end.

Finish - Powder coated to match the fixture unless specified different.

Consult factory for additional details or other pole options.

