GOLD CUP MD LED

Architectural Outdoor





FEATURES


- Cast Aluminum Housing w/ Textured Polyester Bronze Powder Coat Finish
- Ribbed Borosilicate Glass Diffuser
- Fully Gasketed
- Stainless Steel ZInc-Coated Screws
- Mounts Direct to Flat Surface w/ Four #8 Wall Anchors (Not Included)

PROJECT: TYPE: PO#:

COMMENTS:

- Cast-In Template
- L70 Life Time For 50,000hr
- CSA Listed Wet Location For Wall Mounting
- Emergency Battery Available
- LED Light Fixture
- Mounting Hardware Included





FINISHES Antique Antique Bronze Matte Metallic Copper Silver Mist Silver Black Sand Swedish Textured Textured Textured White Steel Black Bronze For RAL Colors & Custom Match -Contact Teron Lighting Inc.



TERONLIGHTING.COM 33 DONALD DR, FAIRFIELD, OH 45014 P: 513.858.6004 F: 513.858.6038 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

QTY:

GOLD CUP MD LED

Architectural Outdoor

() 🗎 💷 Ŧ

PROJECT:		
TYPE:		
PO#:	QTY:	
COMMENTS:		

Fixture Core				
PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER	
GPM - Gold Cup MD	L35.0 - 35W LED Module	100 - 277V	Not Applicable	
ORDER INFO				
GPM	L35.0	100 - 277V	Not Applicable	

Example ^ (may not represent a manufacturable product)

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable ORDER INFO	AC - Antique Copper AS - Antique Silver Bronze (Standard) BT - Bronze Mist MB - Metallic Black SM - Matte Silver SN - Sand SW - Swedish Steel TB - Textured Black	50K - 5000K Color Temp	CGL - Clear Glass Lens (Standard) DIM - Dimmable Driver (0 - 10V) PDIM - Pulse Width Dimmable Driver (0 - 10V) SDIM - Step-Dimmable Driver (Dimmable to 25% and 50%) PCL120 - Photocell 120V PCL277 - Photocell 277V LXS - Lexan Lens Shield VS - Internal Cut-off Visor WGD - Steel Wire Guard TP - Tamper-Proof Screw Set F - Fused EB - Bodine BSL23 - Will light Two 5.5W LED Strips (Please Specify Voltage) SPD - Surge Protection Device
Not Applicable	AC	40K	CGL

Example ^ (may not represent a manufacturable product)

PROD	SOURCE	40K SPECS	50K SPECS		
GPM	L35.0	• 80 CRI Typ. • 40K - 4000K Color Temp • 3990 LED Source Lumens • 114 LED Source Lumans Per Watt	 80 CRI Typ. 50K - 5000K Color Temp 4200 LED Source Lumens 120 LED Source Lumans Per Watt 		

REPLACEMENT PART	PART NO	NOTES
Ribbed Borosilicate Glass Diffuser	37127	
Frosted Ribbed Borosilicate Glass Diffuser	3712762	
Internal Visor (Please Specify Color When Ordering)	5300799	Don't see the configuration you are looking for? Call us today at (513) 858-6004



 TERONLIGHTING.COM

 33 DONALD DR, FAIRFIELD, OH 45014

 P: 513.858.6004
 F: 513.858.6038

 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.