

specter

SPSS MODULES
SNOOT ZOOMABLE 55

bold
lighting



SNOOT ZOOMABLE 55

Our Magnetic track system, SPECTER, is a highly configurable, 2 circuits, 24VDC low voltage track system. Thanks to its magnet mounting technology, the modules are inter-changeable instantaneously. Our track is available in ceiling pendant, surface and recessed mounting for both ceiling and walls. SPECTER track is also available with an optional linear uplight feature. The snoot module complements the SPECTER range with a minimalistic cylinder track-head equipped with a wide range of optics and optical accessories allowing professional scenography lighting.

- Up to 1,800lm delivered output
- Available in 1 diameter size, 2.2"
- Various optical accessories available such as beam shaping lenses and Honeycomb louvers
- Beam options, narrow, medium, flood and wide
- Fixtures designed to mount in SPECTER track
- Available in 2 standard finishes: Black and white

Notes: ¹ Available dimming 0-10V and DALI

Code example: **SPSS-Z**22W-W-Z827-2

STANDARD FINISHES



B

W

DELIVERED LUMEN OUTPUT

Length	Watts	CRI +80				CRI +90			
		2700K	3000K	3500K	4000K	2700K	3000K	3500K	4000K
2.2"	10W	1063lm	1063lm	1145lm	1145lm	749lm	804lm	865lm	927lm

Series	Length		Body Finish		Baffle Finish		Beam Angle		CRI		Color Temp		Circuit					
SPSS-Z	22	2.2"	W	White	W	White	Z	20° - 60°	8	+80	27	2700K	1	1-Circuit				
			B	Black	B	Black					9	+90			30	3000K	2	2-Circuit
			S	Silver	S	Silver									35	3500K		
			Z	Bronze	Z	Bronze									40	4000K		
			X	Custom	X	Custom												




Bold Lighting
4710 Ecton Dr., Marietta, GA 30066, USA
info@boldlighting.us www.boldlighting.us
t: +1-678-903-4061


OPTICAL FLEXIBILITY

Photometric data: Type C Polar Curves


25° Beam Angle



40° Beam Angle



55° Beam Angle



SNOOT ZOOMABLE 55

