



CHIC GLOWING ORB
WITH REFINED CHARM
AND DISTINCT ELEGANCE



Features

- Diameter:** 10" to 22" (nominal)
- Output:** 91 LPW
- Housing:** Spun aluminum
- Lens:** Transmissive, opal acrylic globe
- Mounting:** Cord, stem, or surface
- Driver:** In canopy or remote
- Weight:** 6-12 lb (based on Ø)
- Certification:** UL listed for damp location use
- Warranty:** 5-year limited warranty
- Photometry:** Third-party photometric report and IES files on the website

- Single-piece acrylic globe lens
- Five diameter options allow flexible scaling
- Multi-sphere clusters with custom canopies
- RGBW in standard lumen output range

Project: _____ Type: _____ Date: _____

Order: _____


Example: SPH-18 - SO1 - RGBW35 - DMX - STM36 - GRY-RMT

Order Guide



Lens Ø (in.)	Lumen Output	LED	Driver
10	Standard Output 10" - 22" SO1 1,369 lm 15 W SO2 1,826 lm 20 W SO3 2,282 lm 25 W High Output 18" & 22" HO1 3,195lm 35 W HO2 4,108 lm 45 W (high output not available with SRF mounting)	Static White 830 CRI >80 3000°K 835 CRI >80 3500°K 840 CRI >80 4000°K 930 CRI >90 3000°K 935 CRI >90 3500°K 940 CRI >90 4000°K Dynamic White TW tunable white 2700-6500 °K WD warm dim 2200-3500 °K Red, Green, Blue + White RGBW30 RGBW+3000°K RGBW35 RGBW+3500°K RGBW40 RGBW+4000°K (consult for TW, WD & RGBW)	DIM5 0-10 V/5% DIM.1 0-10 V/.1% TRC TRIAC/ ELV DAL DALI DMX Digital Multiplex (consult factory) Drivers rated 120-277 VAC
12			
16			
18			
22			

Sphere Ø in.	Max Weight
10	6 lbs
12	7 lbs
16	9 lbs
18	10 lbs
22	12 lbs



Mounting	Powder Coat Finish	Cord Color	Options
Power Cord Pendant* PCX power cord suspension X= inches cord length; specify CCN-PCX/X cluster with custom canopy X= inches cord length; specify for each sphere - contact factory for required submittals *cord lengths over 96" include price add-on Stem Pendant** STMX Ø 1/2" rigid stem X= inches stem length; specify in 6" increments CCN-STMX/X cluster with custom canopy X= inches stem length; specify for each sphere in 6" increments - contact factory for required submittals **max individual stem length = 96" Surface SRF surface mount	Powder Coat WHT matte white BLK matte black ASL anodized silver GRY matte gray (RAL 7035) RALX matte RAL color X=code (specify) CCL custom color (provide chip)	Specify cord color when power cord mounting is selected (PCX , CCN-PCX) PCW white PCB black PCS silver braided with clear jacket	RMT remote driver BBU remote battery backup with remote driver

Order Examples

- Stem Pendant: SPH-10 - SO2 - 940 - DIM - **STM42** - WHT
- Cord Pendant: SPH-10 - SO2 - 840 - DIM - **PC60** - WHT - PCW
- RGBW LED: SPH-18 - SO1 - **RGBW35** - **DMX** - STM36 - GRY
- RAL Powder Coat: SPH-18 - HO2 - 840 - DIM - PC36 - **RAL5011** - PCB - RMT
- CCN-PCX (3-Sphere Cluster): SPH-**16/18/22** - SO1 - 935 - DIM - **CCN-PC45/65/25** - ASL - PCS
- CCN-STMX (4-Sphere Cluster): SPH-**10/10/16/22** - SO1 - 930 - DIM - **CCN-STM36/36/48/60** - BLK - RMT

Mounting Selection	Powder Coated Features			
	Canopy	Cap	Stem	Collar
PCX CCN-PCX/X	○	○		
STMX CCN-STMX/X	○	○	○	
SRF				○