



**SPECIFICATIONS**

**MATERIAL & FINISHES**

CANOPY

Hand-Spun, High Purity 0.050" Thick 3003-O Temper Aluminum Canopy

CORD

Cord-Hung Pendants Include 7' of Standard Cord or 5' of Cotton or Cloth Cord, +/- For Socket Orientation

POWDER COAT FINISHES

Polyester Powder Coat Finishes Are Electro-Staticly Applied and Thermocured on the Canopy

WOOD

The Wood Detailing of Our American-Made Lighting Is Handcrafted from Solid Hardwoods by Our In-House Artisans. Custom Woods Are Available upon Request, Please Contact Our Sales Team for Additional Information.

WOOD FINISH

The Finish Is a Hand-Rubbed Danish Oil Which Is Buffed and Waxed to a Natural Sheen Using Pure Carnauba Wax

**CERTIFICATIONS, LISTINGS & WARRANTY**

MAX FIXTURE WEIGHT

5 lbs

MADE IN THE USA

Manufactured and Hand-Crafted in Our 60,000 Square Foot Facility Located in Titusville, FL

WOOD SOURCING AND SUSTAINABILITY

All Wood Is Sourced from North American Suppliers Who Practice Responsible Forestry. With Sustainability in Mind, Our Material Suppliers Have Policies in Place Regarding Planned Felling, Minimum Tree Diameter, and Felling Rotation to Ensure Regrowth.

UL LISTED FOR DAMP LOCATIONS

Dependent on Cord Selection

LIMITED WARRANTY

For Additional Information on Our Limited Warranty, Please See Our Terms & Conditions

**LIGHT SOURCE**

INCANDESCENT

Medium Base E26 Socket, 60W Max, 120 VAC