

REV 09.27.18 BALL JAR PENDANT BARN LIGHT CORD PENDANT COLLECTION Max Weight: 10.0 lbs

PROJECT NAME

PROJECT TYPE \_\_\_\_\_

SPS-0002

## BLE - BALLJAR -


BALLJAR -		-		-	
_	Α		В	-	C

Order Example: BLE - BALLJAR - 400 - CSRW - 400

A - LID FINISH		B - CORDS		C - CEIL	C - CEILING CANOPY FINISH	
	INISH R COAT FINISHES: Black Textured Black White Dark Green Emerald Green Jadite Mint Chartreuse Teal Barn Red Orange Watermelon Blush Pink Magenta Buttery Yellow Sunflower Bronze Chocolate Rust Oil-Rubbed Bronze Royal Blue Navy Cobalt Blue Delphite Blue	CSA LIS SBK SWH CSB CSW CSR CSBW CSBW CSBG CSBP CSGW CSBB NON-CS CBK CRZ CMG TBW TBK TWH TRW TBR TBB	TED CORD OPTIONS: Standard Black Standard White Black Cloth White Cloth Red Cloth Black & White Cloth Black & Gold Cloth Black & Gold Cloth Black & Pink Cloth Gold & White Cloth Black & Brown Cloth Black & Brown Cloth CALISTED CORD OPTIONS: Black Cotton Red Chevron Grey Cotton Black & White Twist Black Cotton Twist White Cotton Twist Red & White Twist Brown Cotton Twist Brown & Beige Twist		ING CANOPY FINISH R COAT FINISHES: Black Textured Black White Dark Green Emerald Green Jadite Mint Chartreuse Teal Barn Red Orange Watermelon Blush Pink Magenta Buttery Yellow Sunflower Bronze Chocolate Rust Oil-Rubbed Bronze Royal Blue Navy Cobalt Blue Delphite Blue	
715 800 805 810 975	Delphite Blue Industrial Grey Charcoal Granite Graphite Galvanized	TRD TPT	Red Cotton Twist Putty Cotton Twist	715 800 805 810 975	Delphite Blue Industrial Grey Charcoal Granite Graphite Galvanized	

## **IMPORTANT:**

## DIMENSIONAL DRAWING



## LIGHT SOURCE

All published luminaire photometric testing performed to IESNA LM-79-08 standards by a NVLAP accredited laboratory. Data is considered to be representative of the configurations shown, within the tolerances allowed by Lighting Facts. To obtain an IES file specific to your project, please contact the factory.

OPTION	WATTAGE	CRI	VOLTAGE	DIMMING
INCANDESCENT (MED E26)				
E26	60W Max	100	120 VAC	Bulb Dependent

SPECIFICATIONS	
DESIGN	<b>CERTIFICATIONS, LISTINGS &amp; WARRANTY</b>
CANOPY Hand-Spun, High Purity 0.050″ Thick 3003-O Temper Aluminum Canopy	MADE IN THE USA Manufactured and Hand-Crafted in Our 60,000 Square Foot Facility Located in Titusville, FL
FINISHES	CSA LISTED FOR DRY LOCATIONS
POWDER COAT FINISHES Polyester Powder Coat Finishes Are Electro-Statically Applied and Thermocured on the Canopy	LIMITED WARRANTY For Additional Information on Our Limited Warranty, Please See Our Terms & Conditions