


L611

INTERIOR
Surface Mount Downlight

● Dry location



Ordering Information

Clear Form

Date : _____

Quantity : _____

Project : _____

Note : _____

Type : _____

Specifications

Luminaire | Example Code: L611-MA

Product Finish ¹

L611

Aluminum Finishes:

MA matte clear anodized

BA black anodized

System Components (Ordered Separately)

Remote Driver : _____

* Consult MP Lighting Website or Factory.

Important Notes

Specification

1. Refer to Appendix or MP Lighting website for complete look of luminaire with different finish options.


Warranty Notes & Disclaimer

Malfunction and damage to product due to incompatible dimming system or misuse will not be covered under warranty. Consult MP Lighting for recommended drivers. If the fixture has an option to be installed with a dimming control system, consult a dimming system manufacturer with minimum load before installing. MP Lighting reserves the right, at its sole discretion, at any time and without notice, to make design changes to any of our products. Consult MP Lighting website for most updated documentation.

L611

INTERIOR
Surface Mount Downlight

● Dry location



Application

Environment	Dry Location approved. IP 20.
Mounting	Mounts to 4" octagonal back box with an adaptor

Luminaire Construction

LED Light Source	Lamp supplied by others. Suggested: GU10 LED lamps, GU10 Halogen Lamps.
Weight	N/A
Material	Fixture: Machined aluminum with electroplated finish.
Supplied with	Standard installation housing: Comes with an adapter plate, two #8-32 screws, and wire nuts.
Warranty & LED Life	5 years limited warranty. Estimated useful life of LED is 50,000 hours.

Ordered Separately

System Components	Lamp supplied by others. Suggested: GU10 LED lamps, GU10 Halogen Lamps.
-------------------	---




Mounting Options & Dimensions

LED Fixture Dimensions

Fixture

Bottom View

3D View



Appendix

Aluminum Finishes



MA matte clear anodized



BA black anodized