P₀2DC

INTERIOR

Pendant | For ceilings

Dry location





Ordering Information Clear Form					
Date:					Quantity:
Project:					Note:
Type:					
					
Speci	fications				
Luminaire Example Code: P02-DC-FR-2-C72-MC					
Product	Mounting	Shade	Size	Cord ¹	Hardware Finish
P02	DC		2		
	DC dual circuit	SM solid metal FR frosted glass	2 2-3/4" (70mm) tall	Cord: C72 72" (1830mm) CX custom length	MC matte chrome BN brushed nickel
System Components (Ordered Separately)					
Remote Driver :					* Consult MP Lighting Website or Factory.
Important Notes					
Specification 1. 72" (1830mm) cord included. Consult factory for custom cord length. Warranty Notes & Disclaimer					

Malfunction and damage to product due to incompatible dimming system or misuse will not be covered under warranty. Consult MP Lighting for recommended drivers. If the fixture has an option to be installed with a dimming control system, consult a dimming system manufacturer with minimum load before installing. MP Lighting reserves the right, at its sole discretion, at any time and without notice, to

make design changes to any of our products. Consult MP Lighting website for most updated documentation.

P₀2DC

INTERIOR

Pendant | For ceilings

Dry location





Application

Environment Dry Location approved. IP 20.

Mounting Rotatable and easy to position. Designed for use on MP Dual Circuit system (sold separately).

Luminaire Construction

LED Light Source 12V lamp (not included)

Recommended: MR16 or BI-PIN

Weight N/A

Material Fixture: Opalescent cased glass

Hardware: machined marine-grade aluminum

Supplied with Cord: 72" (1830mm) cord. Consult factory for custom cord length.

Warranty & LED Life 5 years limited warranty

Estimated useful life of LED is 50,000 hours.

Ordered Separately

System Components **Power supplies:** remote driver

Please consult factory or visit <u>Recommended Drivers</u> for available driver options.

Mounting Options & Dimensions

LED Fixture Dimensions

