X06SF

INTERIOR

Spotlight | For ceilings, walls & counters

Dry location





_						
Ordering Information				Clear Form	m	
Date :				Quantity:		
Project:				Note:		
Type:						
0	6 : 1 :					
Specifications						
Luminaire Example Code: X06-SF-1-MC						
Product	Mounting	Stem Length	Finish ¹			
X06	SF					
	SF single rail flushed to wall	1 = 1" (25mm) X custom ²	Aluminum Finishes: MC matte chrome			
System Components (Ordered Separately)						
Remote Driver :				* Consult MP Lighting Website or Factory.		
Important Notes						
	Specification 1. Refer to Appendix or MP Lighting website for complete look of luminaire with different finish					

2. Available in 1" (25mm) increments, maximum length 96" (2438mm).

Warranty Notes & Disclaimer

Malfunction and damage to product due to incompatible dimming system or misuse will not be covered under warranty. Consult MP Lighting for recommended drivers. If the fixture has an option to be installed with a dimming control system, consult a dimming system manufacturer with minimum load before installing. MP Lighting reserves the right, at its sole discretion, at any time and without notice, to make design changes to any of our products. Consult MP Lighting website for most updated documentation.

X06SF

INTERIOR

Spotlight | For ceilings, walls & counters

Dry location





Application

Environment Dry Location approved. IP 20.

Mounting SF: Rotatable and easy to position. Designed for use on MP single rail flush wall (SF) rail system (sold separately).

Luminaire Construction

LED Light Source Lamp supplied by others.

Recommended: MR16, 50 W max or LED MR16 (SORAA lamp) 10W max.

Weight N/A

Material Fixture: Machined aluminum with electroplated finish.

Supplied with Standard installation housing: Comes with an adapter plate, two #8-32 screws, and wire nuts.

Warranty & LED Life 5 years limited warranty.

Estimated useful life of LED is 50,000 hours.

Ordered Separately

System Components Lamp.

Mounting Options & Dimensions

LED Fixture Dimensions

Fixture 3D View Beam (with lamp supplied by others)

7-3/8"(187mm) max.

6-1/2"(165mm)

111mm

4-3/8"

111mm

SF

Single Rail Flush to Wall

Fixture with Single Rail Flush

Dimensions



Appendix

Aluminum Finishes



MC matte chrome