


FLINDT GARDEN BOLLARD

Designed by Christian Flindt



Description

The fixture emits a wide downward directed glare-free light. The light source rests at the top inside the asymmetric carving on the side of the bollard, where the gradient serves as a reflector that softens the light and forms a pleasant organic shape on the ground below.

Variants

VARIANT NUMBER	COLOR, RAL	W / H / L (IN) / W (LB)
10000158330	NAT PAINT ALU, 162	- / - / - IN / 5.2 LB
10000158331	CORTEN COLOR, 954	- / - / - IN / 5.2 LB
10000158334	NAT PAINT ALU, 162	- / - / - IN / 5.2 LB
10000158335	CORTEN COLOR, 954	- / - / - IN / 5.2 LB
10000158336	NAT PAINT ALU, 162	- / - / - IN / 5.2 LB
10000158337	CORTEN COLOR, 954	- / - / - IN / 5.2 LB
10000158340	NAT PAINT ALU, 162	- / - / - IN / 5.2 LB
10000158341	CORTEN COLOR, 954	- / - / - IN / 5.2 LB
5747402474	CORTEN COLOR, 954	2 / 13.7 / 2 IN / 2.8 LB
5747402487	CORTEN COLOR, 954	2 / 13.7 / 2 IN / 2.8 LB
5747402500	CORTEN COLOR, 954	2 / 13.7 / 2 IN / 3.2 LB
5747402513	CORTEN COLOR, 954	2 / 13.7 / 2 IN / 5.2 LB
5747402568	CORTEN COLOR, 954	2 / 27.5 / 2 IN / 2.9 LB
5747402571	CORTEN COLOR, 954	2 / 27.5 / 2 IN / 2.9 LB
5747402597	CORTEN COLOR, 954	2 / 37.8 / 2 IN / 3.4 LB
5747402607	CORTEN COLOR, 954	2 / 37.8 / 2 IN / 5.4 LB
5747402830	NAT PAINT ALU, 162	2 / 13.7 / 2 IN / 2.8 LB
5747402843	NAT PAINT ALU, 162	2 / 13.7 / 2 IN / 2.8 LB

5747402869	NAT PAINT ALU, 162	2 / 13.7 / 2 IN / 5.2 LB
5747402872	NAT PAINT ALU, 162	2 / 13.7 / 2 IN / 3.2 LB
5747402924	NAT PAINT ALU, 162	2 / 27.5 / 2 IN / 2.9 LB
5747402937	NAT PAINT ALU, 162	2 / 27.5 / 2 IN / 2.9 LB
5747402953	NAT PAINT ALU, 162	2 / 37.8 / 2 IN / 3.4 LB
5747402966	NAT PAINT ALU, 162	2 / 37.8 / 2 IN / 3.4 LB
5747408782	BLK, 731	- / - / - IN / 3.2 LB
5747408795	BLK, 731	- / - / - IN / 3.2 LB
5747408818	BLK, 731	- / - / - IN / 4.0 LB
5747408821	BLK, 731	- / - / - IN / 4.0 LB
5747408847	BLK, 731	2 / 13.7 / 2 IN / 2.1 LB
5747408850	BLK, 731	2 / 13.7 / 2 IN / 2.1 LB
5747408876	BLK, 731	2 / 13.7 / 2 IN / 2.2 LB
5747408889	BLK, 731	2 / 13.7 / 2 IN / 2.2 LB
5747408902	BLK, 731	2 / 13.7 / 2 IN / 3.1 LB
5747408915	BLK, 731	2 / 13.7 / 2 IN / 3.1 LB
5747408931	BLK, 731	2 / 27.5 / 2 IN / 2.9 LB
5747408944	BLK, 731	2 / 27.5 / 2 IN / 2.9 LB
5747408960	BLK, 731	2 / 37.8 / 2 IN / 3.1 LB
5747408973	BLK, 731	2 / 37.8 / 2 IN / 3.1 LB
5747408999	BLK, 731	2 / 37.8 / 2 IN / 3.9 LB
5747409008	BLK, 731	2 / 37.8 / 2 IN / 3.9 LB

Materials & Finishes

MATERIALS

Top: Cast aluminum. Reflector part: Cast aluminum. Post: Extruded aluminum. Base plate: Cast aluminum.

FINISHES

Natural painted aluminum or corten colored. Textured surface, powder coated.

Mounting

The bollard requires a separate, 24V DC power supply.

Choice of 3 different mounting types.

Spike mounted bollard(Plug&Play): For use in soil or gravel; includes weather-proof cables and connectors for above-ground runs.

Anchor mounted bollard(certified electrician): for casting in new concrete pad.

Base mounted bollard(certified electrician): Includes baseplate for anchoring to decks and floors.

Anchor or Base mounted bollards: installation determined by certified electrician with below ground cabling and conduit. For mounting instructions, see download section on the product detail page.

Information

Electrical:

System Wattage: 6.5W

LED Wattage: 6.0W

Delivered lumens: 215-291 lm

Efficacy: 33.1 - 44.7 lm/W

Certifications:


cULus, Wet Location
 Protection class IP65
 IK class 06
 BUG Rating: B0-U2-G0
 Color Rendering: Ra≥80
 LED is non-dimming.

Low Voltage power supply 24VDC is remote mounted for multiple bollards per supply. Spike mounted bollards use provided weather-proof cables and connectors for above-ground runs. Plug and play.


Anchor or Base mounted bollards: installation determined by certified electrician with below ground cabling and conduit. Consult factory for remote power supply information; maximum bollards and cable distances. For the E-socket product variants, bulbs are not included. LED light source is part of the product.

Light distribution diagrams


CARTESIAN




ISOLUX



POLAR



BUG



Variant Options

For particular variant options, please check our online Product Variants Configurator on the product detail page.

VARIANT NO.	LIGHT SOURCE	VOLTAGE/FRQ	LUMEN	FEATURES	CABLE
10000158330	LED 3000K 6.5W	24V	252	-	-
10000158331	LED 3000K 6.5W	24V	215	-	-
10000158334	LED 2700K 6.5W	24V	252	-	-
10000158335	LED 2700K 6.5W	24V	215	-	-
10000158336	LED 3000K 6.5W	24V	252	-	-
10000158337	LED 3000K 6.5W	24V	215	-	-
10000158340	LED 2700K 6.5W	24V	252	-	-
10000158341	LED 2700K 6.5W	24V	215	-	-
5747402474	LED 3000K 6.5W	24V	215	-	-
5747402487	LED 2700K 6.5W	24V	215	-	-
5747402500	LED 3000K 6.5W	24V	215	-	-
5747402513	LED 2700K 6.5W	24V	215	-	-
5747402568	LED 3000K 6.5W	24V	215	-	-
5747402571	LED 2700K 6.5W	24V	215	-	-
5747402597	LED 3000K 6.5W	24V	215	-	-

louis poulsen

5747402607	LED 2700K 6.5W	24V	215	-	-
5747402830	LED 3000K 6.5W	24V	252	-	-
5747402843	LED 2700K 6.5W	24V	252	-	-
5747402869	LED 3000K 6.5W	24V	252	-	-
5747402872	LED 2700K 6.5W	24V	252	-	-
5747402924	LED 3000K 6.5W	24V	252	-	-
5747402937	LED 2700K 6.5W	24V	252	-	-
5747402953	LED 3000K 6.5W	24V	252	-	-
5747402966	LED 2700K 6.5W	24V	252	-	-
5747408782	LED 3000K 6.5W	24V	-	-	-
5747408795	LED 2700K 6.5W	24V	-	-	-
5747408818	LED 3000K 6.5W	24V	-	-	-
5747408821	LED 2700K 6.5W	24V	-	-	-
5747408847	LED 3000K 6.5W	24V	-	-	-
5747408850	LED 2700K 6.5W	24V	-	-	-
5747408876	LED 3000K 6.5W	24V	-	-	-
5747408889	LED 2700K 6.5W	24V	-	-	-
5747408902	LED 3000K 6.5W	24V	-	-	-
5747408915	LED 2700K 6.5W	24V	-	-	-
5747408931	LED 3000K 6.5W	24V	-	-	-
5747408944	LED 2700K 6.5W	24V	-	-	-
5747408960	LED 3000K 6.5W	24V	-	-	-
5747408973	LED 2700K 6.5W	24V	-	-	-
5747408999	LED 3000K 6.5W	24V	-	-	-
5747409008	LED 2700K 6.5W	24V	-	-	-
