


# LP ICON CABLE HANGER

**Project name:**

**Project type:**

**Notes:**



## Design

Mads Odgård

## Product description

Moderately sized post top luminaire that combines the geometries of a half dome with vertical cylinder. Opal white, impact-resistant acrylic casts a glowing effect that emulates the moon. Choice of optics for Type II or Type V distributions.

## Variant options

**Light source**

LED 3000K 76W  
LED 4000K 76W

**Lumen**

7029  
7204  
7267  
7449

**Voltage frequency**

120-277V/60HZ

**Distribution/Trim**

ASYT3  
ROTS

**Lighting control**

Dim 0-10v  
Sr nema

## Light description

The fixture provides mainly direct downward illumination. The shade is lit up from within and creates a soft diffuse upwards light. Choice of symmetric or asymmetric light distributions. Standard CCT in 3000K or 4000K, controlled by electronic dimmable driver.

## Mounting

Suspension type: Suspended from a provided through-wiring cable hanger. (Suspension cables by others.)

## Information

Electrical:  
 System Wattage: 76 W  
 LED Wattage: 73 W  
 Delivered lumens: 7,029 lm - 7,449 lm  
 Efficacy: 92.4 - 98.0 lm/W  
 Certifications:  
 cULus, Wet Location  
 Protection class IP65  
 IK class 06  
 BUG Rating: B2-U2-G0; B1-U2-G1  
 Controllability: 0-10V Dimming Min.-Max. Ambient Temp: -20°C to +70°C  
 Color Rendering: Ra≥80  
 Please contact Louis Poulsen for 2700K.

## Finish

Natural paint aluminum


## Voltage

120-277V/60HZ


## Light distribution diagrams

For the full data set on all variants, see [louispoulsen.com](http://louispoulsen.com).


Cartesian




Isolux



Polar



Bug



## Material

Housing: Die cast aluminum, 0.12" thick. Dome-shaped shade: Translucent injection molded opal, impact-resistant acrylic, 0.12" thick. Bottom lens: clear, tempered safety glass with safety-cable, partially silk-screened. Latches: Spring strength stainless steel. Standard finish is matte, textured surface powder coat with minimum 2 mils thickness in natural painted aluminum.

## Weight

Min: 29.013 lbs Max: 29.013 lbs

## Other functions

LED in 2700K or 3500K. Amber LED available for sea turtle nesting areas. Surge protector with 10,000 Amp current rating. Dark Sky Compliant (BUG U=0). Custom finishes. Alternative dimming controls, including wireless systems. A Retrofit Kit is available for updating conventional LP Icon variants to LED.

## Specification notes

- a. 45W LED variant only available with T5 distribution and polished reflector.
- b. 57W LED variant only available with T2 distribution and matte reflector.

## Variant options

Light source	Lumen	Voltage frequency	Distribution/Trim	Lighting control	Variant number
LED 3000K 76W	7029	120-277V/60HZ	ASYT3	Dim 0-10v	10000157334
LED 3000K 76W	7204	120-277V/60HZ	ROT5	Dim 0-10v	10000157335
LED 4000K 76W	7267	120-277V/60HZ	ASYT3	Dim 0-10v	10000157336
LED 4000K 76W	7449	120-277V/60HZ	ROT5	Dim 0-10v	10000157337
LED 3000K 76W	7029	120-277V/60HZ	ASYT3	Sr nema	10000157338
LED 4000K 76W	7267	120-277V/60HZ	ASYT3	Sr nema	10000157339