## CAPRI LED 24"

Architectural Indoor





### PROJECT: TYPE: COMMENTS:

QTY:

### **FEATURES**

- ADA Compliant
- CSA Listed Damp Location For Wall or Ceiling Mounting

PO#:

- L22.0 and L33.0 are Dimmable at 120V Only
- LED Light Fixture
- Luminous White Acrylic Diffuser
- Mounts Directly to Surface w/ Two Wall Anchors (Not Included)
- Steel Housing w/ Matte Silver Powder Coat Finish
- Steel Mounting Pan w/ Hi-Reflectance White Powder Coat Finish
- Steel Reflector w/ Hi-Reflectance White Powder Coat Finish

	LINE DRA	WING			LINE DR	AWING NOT TO SCALE
			<b>24 7/8</b> 36 7/8'		•	
			48 7/8			
C					5 3/4"	
	FINISHES Antique	Antique	Bronze	Matte	Sand	Swedish
	Copper	Silver	Mist	Silver		Steel
	Textured Black	Textured Bronze	Textured White			
						For RAL Colors & Custom Match - <b>Contact Teron</b> Lighting Inc.



TERONLIGHTING.COM 33 DONALD DR, FAIRFIELD, OH 45014 P: 513.858.6004 F: 513.858.6038 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

## CAPRI LED 24"

Architectural Indoor

# £ 🕀 📼

#### PROJECT: TYPE: PO#: QTY: COMMENTS:

Fixture Core			
PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
CPR24 - Capri 24"	L22.0-LT700 - 22W @ 700mA ELV Dimming Driver (Dimmable at 120V Only) L33.0-LT1000 - 33W @ 1000mA ELV Dimming Driver (Dimmable at 120V Only) L33.0-ZE1000 - 33W @ 1000mA 0-10V Dimming Driver L36.0-ZE1100 - 36W @ 1100mA 0-10V Dimming Driver	120V 277V	Not Applicable
CPR24	L22.0-LT700	120V	Not Applicable

#### esthetics & Ontions

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	AC - Antique CopperTB - Text BlackAS - Antique SilverBlackBT - Bronze MistBZ - Text BronzeSM - Matte Silver (Standard)TW - Tex 	ured <b>35K</b> - 3500K Color Temp <b>40K</b> - 4000K Color Temp	<b>F</b> - Fused <b>TP</b> - Tamper Resistant Screws
Not Applicable Example ^	AC	27К	F

PROD	SOURCE	30K SPECS
CPR 24"	L22.0	30K - 3000K Color Temp 3479 LED Source Lumens 145 LED Source Lumens Per Watt
	L33.0	30K - 3000K Color Temp 4970 LED Source Lumens 145 LED Source Lumens Per Watt
	L36.0	30K - 3000K Color Temp 5467 LED Source Lumens 145 LED Source Lumens Per Watt

REPLACEMENT PART White 2' Acrylic Diffuser

3039860 Don't see the configuration you are looking for? Call us today at (513) 858-6004



TERONLIGHTING.COM 33 DONALD DR, FAIRFIELD, OH 45014 P: 513.858.6004 F: 513.858.6038 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice. 2