VICEROY LG LED 24"

Architectural Indoor

6. D i 🖸



PROJECT: TYPE: COMMENTS:

QTY:

FEATURES

• Steel Housing with Matte Silver Powder Coat Finish

PO#:

- Matte White Acrylic Inner Diffuser
- Clear Acrylic Outer Diffuser
- 0-10V and Trailing Edge (ELV) Dimming Compatible Options Available
- Over-Voltage, Over-Current, and Short-Circuit Protection with Auto Recovery
- Mounts Directly to Surface with Two Wall Anchors (Not Included) Over a 2" Junction Box (Not Included)
- L70 Life Time For 50,000hr
- Knockouts on Back Accept Standard Electrical Fittings (By Others)
- ADA Compliant
- CSA Listed Damp Location For Wall or Ceiling Mount
- LED Light Fixture

LINE DRAWING				LINE DRAWING NOT TO SCALE		
		3	26" 38"	4 "	 _	
					` <i>4"</i>	
FINISHES					,	
Antique Copper	Antique Silver	Bronze Mist	Matte Silver	Sand	Swedish Steel	
Textured Black	Textured Bronze	Textured White			For RAL Colors & Custom Match - Contact Teron Lighting Inc.	



TERONLIGHTING.COM 33 DONALD DR, FAIRFIELD, OH 45014 P: 513.858.6004 F: 513.858.6038 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice. 1

VICEROY LG LED 24"

Architectural Indoor

L 🕀 🖬 📼

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

Fixture Core			
PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
VCYL24 - Viceroy LG 24"	L20.1-TE550 - 30W LED Strip(s) @ 550mA ELV Dimming Driver L20.1-ZE550 - 22W LED Strip(s) @ 550mA Line Voltage 4-Wire Dimming Driver (Dimmable 0 - 10V)	347V (L20.1-ZE550 Only)	Not Applicable
		400.0771	
VCYL24	L20.1-TE550	120-277V	Not Applicable

Aesthetics & Options

TRIM		FINISH		COLOR TEMP	ס	OPTIONS		
Not Applicable		AC - Antique Copper AS - Antique Silver BT - Bronze Mist BZ - Textured Bronze SM - Matte Silver (Standard) SN - Sand	AC - Antique CopperSW - Swedish SteelAS - Antique SilverSteelBT - Bronze MistTB - Textured BlackBZ - Textured BronzeTW - Textured WhiteSM - Matte Silver (Standard)SW - Matte Silver		color Temp color Temp color Temp color Temp	(Field Instal F - Fused (1 JBC - Junctio	EBR - Remote Mount Battery (Field Installed) F - Fused (120V / 277V Only) JBC - Junction Box Cover TP - Tamper Resistant Screws	
RDER INFO								
Not Applicab	le	AC		30K		EB		
Example ^								
PROD	SOURCE	30K SPECS						
VCYL24	L20.1	 30K - 3000K Color Temp 2982 LED Source Lumens 148.3 LED Source Lumens Per Watt 						

2' Lens Assembly	38096	Don't see the configuration you are looking for? Call us today at (513) 858-6004
	PART NO	NOTES



TERONLIGHTING.COM 33 DONALD DR, FAIRFIELD, OH 45014 P: 513.858.6004 F: 513.858.6038 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.