

JOB NAME _____

CONTACT _____


ORDERING CODE _____

ORDERING CODES

PART NUMBER	FEATURES	DEGREE	KELVIN	LUMENS
SYS 4W - 700mA				
<i>Order driver separately</i>				
577-00607012305us	white	12°	2700	140
577-00607012306us	black	12°	2700	140
577-00607012308us	matte chrome	12°	2700	140
577-00607012905us	white	12°	3000	150
577-00607012906us	black	12°	3000	150
577-00607012908us	matte chrome	12°	3000	150
577-00607012705us	white	12°	3500	160
577-00607012706us	black	12°	3500	160
577-00607012708us	matte chrome	12°	3500	160
577-00607022305us	white	21°	2700	140
577-00607022306us	black	21°	2700	140
577-00607022308us	matte chrome	21°	2700	140
577-00607022905us	white	21°	3000	150
577-00607022906us	black	21°	3000	150
577-00607022908us	matte chrome	21°	3000	150
577-00607022705us	white	21°	3500	160
577-00607022706us	black	21°	3500	160
577-00607022708us	matte chrome	21°	3500	160

RIDE

Ride Spot 1



Overall trim ring size: 2-1/8"
 Hole cut out size: 1-7/8" or 48mm
 Snoot Length: 1-7/16"
 Snoot diameter: 7/8"
 Fixture recess into hole cutout: 1-3/8"

DRIVER MATRIX

PART NUMBER	DRIVER	QUANTITY	POWER SPEC
P70418-700	36W LED Driver w/ box	for 2-8 fixtures	120-277V, 36W, 700mA, Trailing Edge (ELV) dimming
P70414-700-ECO	50W LED Driver w/ box	for 1-11 fixtures per channel (1 channel driver)	120-277V, 50W, 700mA, 0-10V (1%) dimming
P70414-700-SOLO	50W LED Driver w/ box	for 1-11 fixtures per channel (2 channel driver)	120-277V, 50W, 700mA, 0-10V (.1%) dimming
P70469-700-ECO	50W LED Driver w/ box	for 1-11 fixtures per channel (1 channel driver)	120-277V, 50W, 700mA, DALI (1%) dimming
P70469-700-SOLO	50W LED Driver w/ box	for 1-11 fixtures per channel (2 channel driver)	120-277V, 50W, 700mA, DALI (.1%) dimming
P70470-700	50W LED Driver w/ box	for 1-11 fixtures per channel (3 channel driver)	120-277V, 50W, 700mA, DMX/ ROM (0%) dimming

DESCRIPTION

- Semi-recessed adjustable mini-spot head
- Matte chrome, white or black finish
- 40° tilt and 90° swivel
- 12° or 21° faceted lens
- Single

ELECTRICAL

- 3V, 700 mA constant current (*remote driver required*)

LISTING

- ETLus Listed to UL2108 (*suitable for dry locations only*)
- cETL Listed to CSA C22.2 #9.0
- IP20 rated

LED PERFORMANCE

LED: Lumileds Luxeon Z ES
 SDCM: 3 Step MacAdam Ellipse
 CCT: 2700K, 3000K, or 3500K
 CRI: >90
 Life: L₈₀ 50,000hrs

