

SPECIFICATION SHEET

1633 Staunton Ave Los Angeles, CA 90021

TEL. FAX.

(800) 727-9262 (800) 727-9957 (213) 747-4500 (213) 747-3234

E-Mail: sales@coronalighting.com

PRODUCT #: CL-326-NM

•Well Lights

Wiring:

Composite

Fixture Specifications:

Housing: Injection molded fiberglass for high UV stability.

Finish: Polyester UV powder coated, in BK-Black,

Lens: Clear, tempered and heat resistant convex glass.

Extra flat lens included.

Socket: Top grade ceramic bi-pin socket with retention

clin

Lamp: 12V, MR-16 halogen 20W max. L-BAB-C20 (20w)

standard. LED lamps are also available. See lamp

guide, below for more information.

Gasket: Silicone "0" ring seals faceplate to housing

providing weather tight protection.

vvon Ligitto

Fixture is prewired with a 3ft 18-2 SJT-W direct burial cord. Wire connector sold seperately. Silicone filled wire nut (**CX-854**) is available from

Corona Lighting.

Mounting: In-ground direct burial or concrete encasement.


Electrical Notes: A remote 12V transformer required, may be

ordered to Corona Lighting seperately. Voltage range for 12V halogen lamps are 11V-12.5V Voltage range for LED lamps are 9V-17V.

Warranty: Limited one (1) year warranty on composite fixture

against manufacturer's defects.







AVAILABLE LED LAMPS (Corona LED lamps have a five (5) year limited warranty against manufacturer's defects)

LAMP NUMBER	WATTS	BEAM SPREAD LUMEN		_ COLOR & TEMP.	RATED HOURS	HALOGEN EQUIVALENT
LAWF NUMBER	WALIO	OF INLAD	LOWILIA	I LIVII .	1100110	EQUIVALENT
L-ED16-COB5W-SP	5	15° Spot	450	2700K	50,000	50 Watt
L-ED16-COB5W-FL	5	38° Flood	450	2700K	50,000	50 Watt
L-ED16-COB5W-WF	5	60° Wide Flood	450	2700K	50,000	50 Watt
L-ED16-COB5W-SP3K	5	15° Spot	470	3000K	50,000	50 Watt
L-ED16-COB5W-FL3K	5	38° Flood	470	3000K	50,000	50 Watt
L-ED16-COB5W-WF3K	5	60° Wide Flood	470	3000K	50,000	50 Watt
L-ED16-3W-SP	3.5	15° Spot	270	2700K	50,000	25 Watt
L-ED16-3W-FL	3.5	45° Flood	270	2700K	50,000	25 Watt
L-ED16-3W-WF	3.5	60° Wide Flood	270	2700K	50,000	25 Watt
L-ED16-5W-SP	5	15° Spot	350	2700K	50,000	40 Watt
L-ED16-5W-FL	5	45° Flood	350	2700K	50,000	40 Watt
L-ED16-5W-WF	5	60° Wide Flood	350	2700K	50,000	40 Watt
For more additional Lamps, and accessories visit Coronalighting.com						

JOB INFORMATION

TYPE: DATE:

JOB NAME & ADDRESS:

PRODUCT #:

TOTAL QUANTITY:

LAMP TYPE & WATTAGE:

TRANSFORMER:

CONTRACTOR:

SPECIFIER:

• When ordering LED lamp with a fixture your part number should follow the format below:

• CL - product # - lamp - wattage - lamp angle

CL - 326-NM - L-ED16 - 5W - FL

Example: CL-326-NM-L-ED16-5W-FL

Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixure without further notification.