## BIRDIE OV CA GRL LED

Architectural Outdoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	






#### **FEATURES**

- · Die-Cast Aluminum Housing w/ Matte White Polyester Powder Coat Finish
- Die-Cast Aluminum Grill (Standard) w/ Matte White Polyester Powder Coat Finish
- · Frosted Ribbed Borosilicate Glass Diffuser
- · Front and Back Gasketing
- · Stainless Steel Housing Screws
- Mounts Directly to 4" Junction Box (By Others)
- · CSA Listed Wet Location
- LED Light Fixture
- · Mounting Hardware Included
- · Vandal Resistant

#### LINE DRAWING



Matte

Silver

### **FINISHES**

Antique Copper Textured

Black




Antique

Silver









For RAL Colors & Custom Match -Contact Teron Lighting Inc.





# BIRDIE OV CA GRL LED

Architectural Outdoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

Fixture Core

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER		
BEOC - Birdie OV CA  L13.0-LE350 - 13W @ 350mA Phase Dimming Driver (Dimmable @ 120V Only) (Dimmable to 10%)  L13.0-350 - 13W @ 350mA - 350mA Constant Current Driver		120V 277V (50 / 60Hz)	Not Applicable		
ORDER INFO					
BEOC	L13.0-LE350	120V	Not Applicable		

Example ^ (may not represent a manufacturable product)

#### Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS	
GRL	AC - Antique Copper AS - Antique Silver BT - Bronze Mist SM - Matte Silver SN - Sand SW - Swedish Steel TB - Textured Bronze TW - Textured White WH - Matte White (Standard)	30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp	F - Fused SPD – Surge Protection Device	
ORDER INFO				
GRL	AC	30K	Not Applicable	

Example ^ (may not represent a manufacturable product)

PROD	SOURCE	30K SPECS		
PROD BEOC	SOURCE L13.0	• 30K SPECS  • 30K - 3000K Color Temp  • 1614 LED Source Lumens  • 124.1 LED Source Lumens Per Watt		

REPLACEMENT PART	PART NO	NOTES
Frosted Glass Lens	3700562	
Birdie Oval GRL Fascia (Specify Finish)	5501599	Don't see the configuration you are looking for? Call us today at (513) 858-6004



