CAPRICCIO LED

Architectural Outdoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	






FEATURES

- ADA Compliant
- Aluminum Fascia and Mount Pan w/ Matte Silver Powder Coat Finish
- CSA Listed Wet Location For Wall Mount Only
- Drivers are Constant Current Dimmable 0-10V
- · Frosted White Acrylic Lens Assembly
- · LED Light Fixture
- Mounts Directly to Flat Surface w/ Wall Anchors (By Others)
- Open Top and Bottom
- Self-Contained Waterproof LED Module Assembly
- · UL Class 2 Driver









FINISHES

Antique Copper

Textured Black



Antique Bronze Silver



Textured White



Sand



For RAL Colors & Custom Match -**Contact Teron** Lighting Inc.



CAPRICCIO LED

Architectural Outdoor



F	iχ	t	u	r	е	C	0	re	
---	----	---	---	---	---	---	---	----	--

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	·

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
CPO - Capriccio	L20.0-ZE700 - 20W @ 700mA 0-10V Dimming Driver	120 - 277V (50/60Hz)	Not Applicable
ORDER INFO			
CPO	L20.0-ZE700	120 - 277V	Not Applicable

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	AC - Antique Copper AS - Antique Silver BT - Bronze Mist SM - Matte Silver (Standard) SN - Sand SW - Swedish Steel TB - Textured Black BZ - Textured Bronze TW - Textured White	30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp 50K - 5000K Color Temp	F - Fused SPD – Surge Protection Device
Not Applicable	AC	30K	F

PROD	SOURCE	30K SPECS		
CPO	L20.0	30K SPECS 30K - 3000K Color Temp 2600 LED Source Lumens 130 LED Source Lumens Per Watt		

REPLACEMENT PART	PARINU	NULES
Frosted White Lens Assembly	38115	Don't see the configuration you are looking for? Call us today at (513) 858-6004

