DUVAL LED

Architectural Outdoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	




FEATURES

- Aluminum Housing w/ Polyester Powder Coat Finish
- Aluminum Heat-Sink Plate
- Solid Top and Bottom End Plates
- . Luminous White Acrylic Panels
- Optional Surge Protector
- Mounts Directly to 4" Junction Box (By Others)
- CSA Listed Wet Location
- · LED Light Fixture
- Mounting Hardware Included
- Optional Vandal Resistant

LINE DRAWING

LINE DRAWING NOT TO SCALL



FINISHES



For RAL Colors & Custom Match -Contact Teron Lighting Inc.





DUVAL LED

Architectural Outdoor



PO#: COMMENTS:

PROJECT: TYPE:

Fixture Core

rixture core			
PRODUCT CODE	TRIM	SOURCE/WATTAGE	DIMMING DRIVER
DV - Duval	Not Applicable	L18.0 - 20W	ZE- 0-10V
		L37.0 - 42W	
ORDER INFO			

Example ^ (may not represent a manufacturable product)

Aesthetics & Options

VOLTAGE	FINISH	COLOR TEMP	OPTIONS
UNV - 120 - 277V	AC - Antique Copper AS - Antique Silver BT - Bronze Mist SM - Matte Silver SN - Sand SW - Swedish Steel TB - Textured Black	30K - 3000K Color Temp 40K - 4000K Color Temp 50K - 5000K Color Temp	F - Fused TP - Tamper-Proof Screws SPD – Surge Protection Device
ORDER INFO			

Example ^ (may not represent a manufacturable product)

PROD	SOURCE	SPECS
DV	L18.0	80 CRI Typ. 30K - 3000K Color Temp 899 LED Delivered Lumens 45 LED Source Lumens Per Watt
	L37.0	• 80 CRI Typ. • 30K - 3000K Color Temp • 1826 LED Delivered Lumens • 43 LED Source Lumens Per Watt

REPLACEMENT PART	PART NO	NOTES
White Acrylic Lens Panel Set	9800660	Don't see the configuration you are looking for? Call us today at (513) 858-6004



QTY: