NIKE S LED

Architectural Indoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	






FEATURES

- ADA Compliant
- CSA Listed Dry Location
- Die-Form Cold-Rolled Steel Housing w/ Brushed Nickel Plated Finish
- LED Light Fixture
- Luminous White Acrylic Diffuser
- Mounting Hardware Included
- Mounts Directly to 4" Junction Box (By Others)
- Steel Mounting Pan w/ Hi-Reflectance White Powder Coat Finish
- Steel Trim w/ Brushed Nickel Plated Finish



LINE DRAWING

LINE DRAWING NOT TO SCALE





FINISHES

Antique

Copper
Textured





Sand



Black

TERONLIGHTING.COM

33 DONALD DR, FAIRFIELD, OH 45014

P: 513.858.6004 **F**: 513.858.6038 **E**: SALES@TERONLIGHT.COM





For RAL Colors & Custom Match -Contact Teron Lighting Inc.





NIKE S LED

Architectural Indoor



☎		
42	(LED)	7
ui.		7

Tixture core				
PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER	
NES - Nike S	L10.5-TL350 - (40) LED Array @ 350mA ELV or Triac Dimming Driver (120v Only) L10.5 - (40) LED Array	120V 277V (50 / 60Hz)	Not Applicable	
ORDER INFO				
	140 5 17050	4001	A1 - A - II - I I	
NES	L10.5-LT350	120V	Not Applicable	
Example ^				

PROJECT: TYPE:

COMMENTS:

QTY:

PO#:

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	AC - Antique Copper AS - Antique Silver BT - Bronze Mist BN - Brushed Nickel SM - Matte Silver SN - Sand SW - Swedish Steel TB - Textured Black	30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp	F - Fused
ORDER INFO			
Not Applicable	AC	27K	F

PROD	SOURCE	30K SPECS		
NES	L10.5	30K SPECS 30K - 3000K Color Temp 1158 LED Source Lumens 58 LED Source Lumens Per Watt		

REPLACEMENT PART	PART NO	NOTES
White Acrylic Diffuser	3049860	TL350 is for 120v only
		Don't see the configuration you are looking for? Call us today at (513) 858-6004

