ROYAL CNC LED

Architectural Outdoor

36	ED	Z

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	·






FEATURES

- · Aluminum Reflector
- · CSA Listed Wet Location
- · LED Light Fixture
- Luminous White 75% DR Acrylic Diffuser
- · Mounting Hardware Included
- Mounts Directly to 4" Junction Box (By Others)
- · Steel Fascia w/ Textured Black Polyester Powder Coat Finish
- Steel Mounting Pan w/ Hi-Reflectance White Powder Coat Finish



LINE DRAWING







FINISHES

Antique Copper

Antique Silver





Sand



Textured Black



Textured **Bronze**



Textured White

For RAL Colors & Custom Match -Contact Teron Lighting Inc.







ROYAL CNC LED

Architectural Outdoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

Fixture Core

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
RL - Royal ORDER INFO	L15.0-TE600 - 15.0W @ 600mA ELV Dimming Driver L18.0-TE700 - 18.0W @ 700mA ELV Dimming Driver L18.0-ZE700 - 18.0W @ 700mA Line Voltage 4-Wire Dimming Driver (Dimmable 0 - 10V)		Not Applicable
ONDER INI O			
RI	L15.0-TE600	120V	Not Applicable

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
CNC	AC - Antique Copper AS - Antique Silver BT - Bronze Mist SM - Matte Silver SN - Sand SW - Swedish Steel TB - Textured Black (Standard)	30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp	F - Fused TP - Tamper Resistant Screws SPD – Surge Protection Device
ORDER INFO			
CNC	AC	30K	F

Example ^ (may not represent a manufacturable product)

PROD	SOURCE			
RL	L15.0	• 30K - 3000K Color Temp • 2048 LED Source Lumens • 136.5 LED Source Lumans Per Watt		
	L18.0	• 30K - 3000K Color Temp • 2390 LED Source Lumens • 132.8 LED Source Lumans Per Watt		

REPLACEMENT PART	PART NO	NOTES
White 75% DR Acrylic Lens	3051060	Don't see the configuration you are looking for? Call us today at (513) 858-6004





ROYAL CNC LED

Architectural Outdoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

Fixture Core

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
RL - Royal	L30.0-ZE1050 - 30.0W @ 1050mA Line Voltage 4-Wire Dimming Driver (Dimmable 0 - 10V)	120V 277V (50 / 60Hz)	Not Applicable
ORDER INFO			
RL	L15.0-TE600	120V	Not Applicable

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
CNC	AC - Antique Copper AS - Antique Silver BT - Bronze Mist SM - Matte Silver SN - Sand SW - Swedish Steel TB - Textured Black (Standard)	30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp	F - Fused TP - Tamper Resistant Screws SPD – Surge Protection Device
ORDER INFO			
CNC	AC	30K	F

Example ^ (may not represent a manufacturable product)

PROD	SOURCE	30K SPECS		
PROD RL	L30.0	30K SPECS • 30K - 3000K Color Temp • 3585 LED Source Lumens • 119.5 LED Source Lumans Per Watt		

REPLACEMENT PART	PART NO	NOTES
White 75% DR Acrylic Lens	3051060	Don't see the configuration you are looking for? Call us today at (513) 858-6004





Example ^ (may not represent a manufacturable product)