ROYAL TWB LED

Architectural Outdoor





FEATURES

- Aluminum Reflector
- CSA Listed Wet Location
- LED Light Fixture
- Luminous White 75% DR Acrylic Diffuser
- Mounting Hardware Included
- Mounts Directly to 4" Junction Box (By Others)
- Steel Fascia w/ Textured Black Polyester Powder Coat Finish

PROJECT: TYPE:

COMMENTS:


PO#:


Steel Mounting Pan w/ Hi-Reflectance White Powder Coat Finish

LINE DRAWING

LINE DRAWING NOT TO SCALE











TERONLIGHTING.COM 33 DONALD DR, FAIRFIELD, OH 45014 P: 513.858.6004 F: 513.858.6038 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

QTY:

ROYAL TWB LED

Architectural Outdoor

SH 💷 Ŧ

PROJECT: QTY: COMMENTS:

Fixture Core			
PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
RL - Royal ORDER INFO	L15.0-TE600 - 15.0W @ 600mA ELV Dimming Driver L18.0-TE700 - 18.0W @ 700mA ELV Dimming Driver L18.0-ZE700 - 18.0W @ 700mA Line Voltage 4-Wire Dimming Driver (Dimmable 0 - 10V)	120V 277V (50 / 60Hz)	Not Applicable
RL	L15.0-TE600	120V	Not Applicable

TYPE:

PO#:

Aesthetics & Options

TRIM		FINISH		COLOR TEMP		OPTIONS	
TWB		AS - Antique Silver Bronze	AC - Antique Copper BZ - Textured Bronze 30K - 3000K Color Temp 35K - 3500K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp 40K - 4000K Color Temp 40K - 4000K Color Temp 50N - Sand 5W - Swedish Steel FB - Textured Black			F - Fused TP - Tamper Resistant Screws SPD – Surge Protection Device	
ORDER INFO							
TWB		AC		30K		F	
Example ^ (r	nay not represent a ma	nufacturable product)					
PROD	SOURCE						
RL	L18.0	30K - 3000K Color Temp 2048 LED Source Lumens 136.5 LED Source Lumans Per Watt 30K - 3000K Color Temp 2390 LED Source Lumens 132.8 LED Source Lumans Per Watt					

REPLACEMENT PART	PART NO	NOTES
White 75% DR Acrylic Lens	3051060	Don't see the configuration you are looking for? Call us today at (513) 858-6004



TERONLIGHTING.COM 33 DONALD DR, FAIRFIELD, OH 45014 P: 513.858.6004 F: 513.858.6038 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

ROYAL TWB LED

Architectural Outdoor

SI 💷 Ŧ

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

Fixture Core			
PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
RL - Royal	L30.0-ZE1050 - 30.0W @ 1050mA Line Voltage 4-Wire Dimming Driver (Dimmable 0 - 10V)	120V 277V (50 / 60Hz)	Not Applicable
ORDER INFO			
RL	L15.0-TE600	120V	Not Applicable

Aesthetics & Options

TRIM		FINISH		COLOR TEMP		OPTIONS		
TWB		BT - Bronze Mist	8Z - Textured Bronze TW - Textured White	30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp		F - Fused TP - Tamper Resistant Screws SPD – Surge Protection Device		
ORDER INFO								
TWB		AC		30K		F		
		nanufacturable product)						
PROD	SOURCE	30K SPECS						
RL	L30.0	30K SPECS • 30K - 3000K Color Temp • 3585 LED Source Lumens • 119.5 LED Source Lumans Per Watt						
REPLACE	MENT PART	PART NO NOT	TES					

REPLACEMENT PART	PARINO	NOTES
White 75% DR Acrylic Lens	3051060	Don't see the configuration you are looking for? Call us today at (513) 858-6004



TERONLIGHTING.COM 33 DONALD DR, FAIRFIELD, OH 45014 P: 513.858.6004 F: 513.858.6038 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.