Architectural Indoor

رگے	(I)	LED	11.

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	




FEATURES

- ADA Compliant
- Centered Over and Mounted to 4" J-Box (By Others)
- CSA Listed Dry Location For Wall Mount
- Dimmable to 10%
- Luminous White Acrylic Diffuser
- · Mounting Hardware Included
- · Open Top and Bottom
- Optional Surge Protector
- Steel Fascia with Matte Silver Powder Coat Finish
- Steel Mounting Plate Mounts to Flat Surface

LINE DRAWING

LINE DRAWING NOT TO SCALE



FINISHES Antique Swedish Antique Bronze Matte Sand Copper Silver Silver Steel Mist Textured Textured Textured Black Bronze White For RAL Colors & Custom Match -**Contact Teron** Lighting Inc.





Architectural Indoor



$\Gamma \cup \pi$.
COMMENTS:

QTY:

PROJECT: TYPE:

Fixture Core

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
TGR - Tiger	L12.0-LT350 - 12.0W LED Strips @ 350mA 2-Wire Trailing or Leading Edge Driver L12.0-ZE350 - 12.0W LED Strips @ 350mA Low Voltage 4-Wire Dimming Electronic Driver	120-277V (120-230V Dimmable For Most LT LED Drivers) (ZE 0-10V Drivers Are Dimmable From 120V - 277V)	Not Applicable
ORDER INFO			
TGR	L12.0-LT350	100-277V	Not Applicable
Evample ^			

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
CNC	AC - Antique Copper AS - Antique Silver BT - Bronze Mist SM - Matte Silver (Standard) SN - Sand SW - Swedish Steel TB - Texte Black BZ - Texte Bronze TW - Text White	35K - 3500K Color Temp 40K - 4000K Color Temp	F - Fused S - Surge Protector TBC - Perforated Steel Top & Bottom Covers TCV - Perforated Steel Top Cover
00000 11100			
ORDER INFO			

Example '

PROD	SOURCE	30K SPECS		
TGR	L12.0	30K - 3000K Color Temp 1400 LED Source Lumens 116.7 LED Source Lumens Per Watt		
	L18.0	30K - 3000K Color Temp 1986 LED Source Lumens 110.3 LED Source Lumens Per Watt		

REPLACEMENT PART	PART NO	NOTES
White Acrylic Lens	3040960	
		Don't see the configuration you are looking for? Call us today at (513) 858-6004





Architectural Indoor



PO#: COMMENTS: QTY:

PROJECT: TYPE:

Fixture Core

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
TGR - Tiger	L18.0-LT500 - 18.0W LED Strips @ 500mA 2-Wire Trailing or Leading Edge Driver L18.0-ZE500 - 18.0W LED Strips @ 500mA Low Voltage 4-Wire Dimming Electronic Driver	120-277V (120-230V Dimmable For Most LT LED Drivers) (ZE 0-10V Drivers Are Dimmable From 120V - 277V)	Not Applicable
ORDER INFO	g		
TGR Example ^	L18.0-ZE500	100-277V	Not Applicable

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
CNC	AC - Antique Copper AS - Antique Silver BT - Bronze Mist SM - Matte Silver (Standard) SN - Sand SW - Swedish Steel TB - Tex Black BZ - Tex Bronze TW - Tey White	35K - 3500K Color Temp 40K - 4000K Color Temp	F - Fused S - Surge Protector TBC - Perforated Steel Top & Bottom Covers TCV - Perforated Steel Top Cover
ORDER INFO			
CNC	I AC	30K	I F

Example '

	PROD	SOURCE	30K SPECS		
	TGR	L18.0	30K - 3000K Color Temp 1986 LED Source Lumens 110.3 LED Source Lumens Per Watt		
_					

REPLACEMENT PART	PARINO	NOTES
White Acrylic Lens	3040960	
		Don't see the configuration you are looking for? Call us today at (513) 858-6004



Architectural Indoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

Fixture Core

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER	
TGR - Tiger	L18.0-ZE500 - 18.0W LED Strips @ 500mA Low Voltage 4-Wire Dimming Electronic Driver	347V (ZE 0-10V Drivers are Dimmable @ 347V)	Dimmable 0-10V	
ORDER INFO				
TOP	140075500	2.471/	Not Appliedble	
TGR Example ^	L18.0-ZE500	347V	Not Applicable	

Aesthetics & Options

TRIM	FINISH		COLOR TEMP	OPTIONS
CNC	AS - Antique Silver BT - Bronze Mist SM - Matte Silver	- Textured onze ' - Textured	30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp 50K - 5000K Color Temp	S - Surge Protector TBC - Perforated Steel Top & Bottom Covers TCV - Perforated Steel Top Cover
ORDER INFO				

Example '

PROD	SOURCE	30K SPECS		
TGR	L18.0	30K - 3000K Color Temp 1986 LED Source Lumens 110.3 LED Source Lumens Per Watt		
				I

REPLACEMENT PART	PART NO	NOTES
White Acrylic Lens	3040960	
		Don't see the configuration you are looking for? Call us today at (513) 858-6004

