Architectural Indoor





#### **FEATURES**

- ADA Compliant
- Centered Over and Mounted to 4" J-Box (By Others)

PROJECT: TYPE: PO#:

COMMENTS:

- CSA Listed Dry Location For Wall Mount
- Dimmable to 10%
- Luminous White Acrylic Diffuser
- Mounting Hardware Included
- Open Top and Bottom
- Optional Surge Protector
- Steel Fascia with Matte Silver Powder Coat Finish
- Steel Mounting Plate Mounts to Flat Surface

#### LINE DRAWING





 TERONLIGHTING.COM

 33 DONALD DR, FAIRFIELD, OH 45014

 P: 513.858.6004
 F: 513.858.6038

 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice. 1

LINE DRAWING NOT TO SCALE

Architectural Indoor

5. St 🗊 Ŧ

## COMMENTS:

QTY:

Fixture Core			
PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
TGR - Tiger	L12.0-LT350 - 12.0W LED Strips @ 350mA 2-Wire Trailing or Leading Edge Driver L12.0-ZE350 - 12.0W LED Strips @ 350mA Low Voltage 4-Wire Dimming Electronic Driver	<b>120-277V</b> (120-230V Dimmable For Most LT LED Drivers) (ZE 0-10V Drivers Are Dimmable From 120V - 277V)	Not Applicable
ORDER INFO			
TGR	L12.0-LT350	100-277V	Not Applicable

PROJECT: TYPE:

PO#:

#### Aesthetics & Options

TRIM		FINISH		COLOR TEMP		OPTIONS	
НСВ		AS - Antique Silver BT - Bronze Mist SM - Matte Silver (Standard)	<b>FB</b> - Textured Black <b>3Z</b> - Textured Bronze <b>FW</b> - Textured White	30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp 50K - 5000K Color Temp	) )	F - Fused S - Surge Pro TBC - Perfora Top & Bottor TCV - Perfora Top Cover	ated Steel n Covers
ORDER INFO							
НСВ		AC		30K		F	
Example ^		1					
PROD	SOURCE	30K SPECS					
TGR	L12.0 L18.0	<ul> <li>30K - 3000K Color Temp</li> <li>1400 LED Source Lumens</li> <li>116.7 LED Source Lumens Per Watt</li> <li>30K - 3000K Color Temp</li> <li>1986 LED Source Lumens</li> <li>110.3 LED Source Lumens Per Watt</li> </ul>					





TERONLIGHTING.COM 33 DONALD DR, FAIRFIELD, OH 45014 P: 513.858.6004 F: 513.858.6038 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

Architectural Indoor

L 🕀 📼 🍹

# COMMENTS:

QTY:

Fixture Core			
PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
TGR - Tiger	L18.0-LT500 - 18.0W LED Strips @ 500mA 2-Wire Trailing or Leading Edge Driver L18.0-ZE500 - 18.0W LED Strips @ 500mA Low Voltage 4-Wire Dimming Electronic Driver	<b>120-277V</b> (120-230V Dimmable For Most LT LED Drivers) (ZE 0-10V Drivers Are Dimmable From 120V - 277V)	Not Applicable
ORDER INFO			
TGR	L18.0-ZE500	100-277V	Not Applicable
Example ^			

PROJECT: TYPE:

PO#:

#### Aesthetics & Options

TRIM		FINISH		COLOR TEMP	01	PTIONS
НСВ		AC - Antique Copper AS - Antique Silver BT - Bronze Mist SM - Matte Silver (Standard) SN - Sand SW - Swedish Steel	TB - Textured Black BZ - Textured Bronze TW - Textured White	30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp 50K - 5000K Color Temp	S - TB To TC	Fused Surge Protector C - Perforated Steel p & Bottom Covers V - Perforated Steel p Cover
ORDER INFO						
НСВ		AC		30K	F	
Example ^		NO		0011		
PROD	SOURCE	30K SPECS				
TGR	L18.0	<ul> <li>30K - 3000K Color Temp</li> <li>1986 LED Source Lumens</li> <li>110.3 LED Source Lumens Per Watt</li> </ul>				

REPLACEMENT PART	PART NO	NOTES
White Acrylic Lens	3040960	
		Don't see the configuration you are looking for? Call us today at (513) 858-6004



TERONLIGHTING.COM 33 DONALD DR, FAIRFIELD, OH 45014 P: 513.858.6004 F: 513.858.6038 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice. 3

Architectural Indoor

### 

QTY:

PO#: COMMENTS:

PROJECT: TYPE:

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER	
TGR - Tiger	<b>L18.0-ZE500</b> - 18.0W LED Strips @ 500mA Low Voltage 4-Wire Dimming Electronic Driver	<b>347V</b> (ZE 0-10V Drivers are Dimmable @ 347V)	Dimmable 0-10V	
ORDER INFO				
TGR	L18.0-ZE500	347V	Not Applicable	
Example ^				
esthetics & Options TRIM	FINISH	COLOR TEMP	OPTIONS	
НСВ	AC - Antique Copper AS - Antique SilverTB - Textured BlackBT - Bronze Mist SM - Matte Silver (Standard)BZ - Textured BronzeSN - Sand SW - Swedish SteelTW - Textured White	30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp 50K - 5000K Color Temp	S - Surge Protector TBC - Perforated Steel Top & Bottom Covers TCV - Perforated Steel Top Cover	
ORDER INFO				
HCB Example ^	AC	30K	F	
PROD SOURCE	30K SPECS			
TGR L18.0	SOK SPECS     SOK - 3000K     Color Temp     1986 LED     Source Lumens     110.3 LED Source			

REPLACEMENT PART White Acrylic Lens 3040960

Lumens Per Watt

Don't see the configuration you are looking for? Call us today at (513) 858-6004



TERONLIGHTING.COM 33 DONALD DR, FAIRFIELD, OH 45014 P: 513.858.6004 F: 513.858.6038 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice. 4