TRITON LED

Architectural Outdoor







FEATURES



· Aluminum Reflector

- Clear Tempered Glass Diffuser
- · CSA Listed Wet Location For Wall Mounting -Down Light only


PROJECT: TYPE: PO#:

COMMENTS:

- Dark Sky Compliant
- · Fully Gasketed
- · Integral Emergency Battery Available
- · LED Light Fixture
- Mounts Direct to Flat Surface w/ Two #8 Wall Anchors (Not Included)
- · Surge Protector

LINE DRAWING

QTY:



FINISHES















Swedish

Steel

For RAL Colors & Custom Match -Contact Teron Lighting Inc.



TERONLIGHTING.COM

P: 513.858.6004

33 DONALD DR, FAIRFIELD, OH 45014

F: 513.858.6038



TRITON LED

Architectural Outdoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

Fixture Core

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER	
TTN - Triton LED	L25.0-ZE700 - 25.0W LED Board @ 700mA Line Voltage 4-Wire Dimming Driver (Dimmable 0 - 10V) L35.0-ZE1050 - 35.0W LED Board @ 1050mA Line Voltage 4-Wire Dimming Driver (Dimmable 0 - 10V)	120-277V (50 / 60Hz)	Not Applicable	
ORDER INFO				
TTN Evample A (may not represent a manufacture)	L25.0-ZE700	120-277V	Not Applicable	

Example ^ (may not represent a manufacturable product)

Aesthetics & Options

TRIM	FINISH		COLOR TEMP	OPTIONS
Not Applicable ORDER INFO	Copper AS - Antique Silver	TB - Textured Black BZ - Textured Bronze (Standard) TW - Textured White	30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp 50K - 5000K Color Temp	EB51 - Integral Emergency Battery EBCA12 - Title 20 Compliant 12 Watt Integral Battery F - Fused PCL120 - Photocell 120V PCL277 - Photocell 277V TP - Tamper Resistant Screws SPD – Surge Protection Device
Not Applicable	AC		30K	EB

Example ^ (may not represent a manufacturable product)

Р	ROD	SOURCE	30K SPECS		
T	ΓN	L25.0	• 30K - 3000K Color Temp • 3072 LED Delivered Lumens • 122.9 LED Delivered Lumens per Watt		
		L35.0	30K - 3000K Color Temp 3898 LED Delivered Lumens 54.2 LED Delivered Lumens per Watt		

REPLACEMENT PART	PART NO	NOTES
Clear Glass Diffuser	37065	
		Don't see the configuration you are looking for? Call us today at (513) 858-6004



