


BASIC NEO
SURFACE



Wall or ceiling mounted LED light, 35 mm tall housing without additional spacers. Direct only light distribution. Opal diffuser made of satin acrylic glass for general lighting. Minimalist design with perfectly uniform lighting. Luminaire body made of aluminum profile optionally available in white, silver, graphite, black, titanium or copper colors. Converter integrated in luminaire housing, switched or dimmed 1-10V. Standard color temperature 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial \leq MacAdam 3. Color rendering CRI $>$ 80, alternative CRI $>$ 90.




D [mm]	D [Inch]
300	11 13/16"
400	1'-3 3/4"
500	1'-7 11/16"
600	1'-11 5/8"

PRODUCT-CODE: 1B A5 O S D - 8 30 M - D300

PRODUCT FAMILY	1B Basic
TYPE	A5 Direct-Only
OPTICAL SYSTEM	O: Opal
SURFACE FINISH	W: Snow White, V: Ivory White, S: Radiant Silver, U: Urban Graphite, B: Jet Black, T: Satin Titanium, K: Satin Copper
CONTROL GEAR	D: 1-10V
Color REEND.	8: CRI $>$ 80, 9: CRI $>$ 90
Color TEMP.	22: 2200K, 27: 2700K, 30: 3000K, 35: 3500K, 40: 4000K, 65: 6500K
POWER	M: Medium Power, H: High Power
SIZE	Luminaire Diameter in mm: D200, D300, D400, D500, D600

OPAL DIFFUSER / DIRECT



D [inch]	Lumen/Watt Medium Power
11 13/16"	1490lm/12W
1'-3 3/4"	1990lm/15W
1'-7 11/16"	2830lm/21W
1'-11 5/8"	4210lm/27W

Lumen Values: Luminaire luminous flux at 4000K/CRI $>$ 80. Other configurations on request.



SNOW WHITE

RADIANT SILVER

URBAN GRAPHITE

JET BLACK

SATIN TITANIUM

SATIN COPPER