


BEAM ME UP JR.
SURFACE



Ceiling mounted LED light, with a setback lens optic in a decorative ring. Ring can be painted in different colors. Direct-indirect or direct only light distribution. Opal diffuser made of satin acrylic glass for general lighting. Minimalist design with perfectly uniform lighting. Indirect component with innovative lens technology for wide-beam ceiling illumination. Luminaire body made of high-quality processed FRP (fiberglass reinforced plastic) in different dimensions. Unique surface finishes optionally available in white, silver, graphite, black, titanium or copper colors. Converter integrated in luminaire housing, switched or dimmed 1-10V. Standard color temperature 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial \leq MacAdam 3. Color rendering CRI > 80, alternative CRI > 90.




D [mm]	D [Inch]	H [mm]	H [Inch]
450	1'-5 23/32"	60	2 3/8"
700	2'-3 18/32"	85	3 11/32"
1100	3'-7 10/32"	125	4 29/32"

PRODUCT-CODE: 1M X3 O B D - 8 30 M - D450 - G


PRODUCT FAMILY	1M: Beam Me Up
TYPE	X3: Direct-Indirect, A3: Direct-Only
OPTICAL SYSTEM	O: Opal
SURFACE FINISH	W: Snow White, V: Ivory White, S: Radiant Silver, U: Urban Graphite, B: Jet Black, T: Satin Titanium, K: Satin Copper
CONTROL GEAR	D: 1-10V
Color REND.	8: CRI>80, 9: CRI>90
Color TEMP.	22: 2200K, 27: 2700K, 30: 3000K, 35: 3500K, 40: 4000K, 65: 6500K
POWER	M: Medium Power, H: High Power
SIZE	Luminaire Diameter in mm: D450, D700, D1100
REFLECTOR	W: Snow White, V: Ivory White, S: Radiant Silver, U: Urban Graphite, B: Jet Black, T: Satin Titanium, K: Satin Copper, G: Satin Gold

OPAL DIFFUSER / DIRECT-INDIRECT



D [inch]	Lumen/Watt Medium Power
1'-5 23/32"	2710lm/24W
2'-3 18/32"	8110lm/78W
3'-7 10/32"	25160lm/178W

OPAL DIFFUSER / DIRECT



D [inch]	Lumen/Watt Medium Power
1'-5 23/32"	1990lm/15W
2'-3 18/32"	4220lm/29W
3'-7 10/32"	14850lm/105W

Lumen Values: Luminaire luminous flux at 4000K/CRI>80. Other configurations on request.

